WATE	D WE	LL RECORD	Form W	WC-5	Division of W	ater Resources App. No	20150382	
		OF WATER WELL:	Fraction	WC-3	Section Number			
				1/ QW 1/	3	T 28 S	R 23 DE WW	
Cou	County: Ford SE 1/4 SE 1/4 SE 1/4 SW 1/4 Street/Rural Address of Well Location; if unknown, distance & direction							
						Global Positioning System (GPS) information:		
from	from nearest town or intersection: If at owner's address, check here $\square$ .					Latitude: 37.63156 (in decimal degrees)		
3 1	3 1/2 West of Ford					Longitude: 099.82450 (in decimal degrees)		
					Elevation:			
2 WATER WELL OWNER: Vincent Oil Corp					Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27			
Villoon Oil Golp					Collection Method:  GPS unit (Make/Model:)			
City, State, ZIP Code : Wichita, KS 67202					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey  Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 213 ft.								
	SECTION BOX: Depth(s) Groundwater Encountered (1)							
SEC	N WELL'S STATIC WATER LEVEL102							
	WELL SSTATIC WATER LEVEL							
	Pump test data: Well water wasft. after hours pumping gpm							
	EST. YIELD. N/Agpm. Well water was							
W								
	WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well							
51	SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
	Irrigation							
ļ <u> </u>	<u> </u>	Was a chemical/	bacteriological sample	e submitted to	Department?	]Yes 🗹 No		
	S If yes, mo/day/yr sample was submitted							
1 mile  Water well disinfected? ✓ Yes ☐ No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .5								
Casing height above land surface. 18 in., Weight SDR-26 lbs./ft., Wall thickness or gauge No.								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From 213 ft. to .20 ft., From ft. to								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From								
What is the nearest source of possible contamination:								
	☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
	Watertig	ht sewer lines 🔲 Seepage p	it 🔲 Feedyard	Fertilizer ste			<del>)</del>	
		n well						
FROM	TO	LITHOLOG	IC LOG	FROM	TO LITHO.	LOG (cont.) or PLU	GGING INTERVALS	
0	4	Top soil						
4	83	Sandy tan clay & sand						
83	124	Sand & gravel- med, co	arse			·		
124	159	Sandy tan clay						
159	203	Sand & gravel- med, tig	ht	<del> </del>	·			
			1111	<del></del>				
203	213	Gray shale						
				<b> </b>				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .11-7-15 and this record is true to the best of my knowledge and helief								
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 12-14-15								
under th	e busine	ss name ofRosencrantz	- Bemis Ent Inc		by (signature)	Some all	A	
INSTRUC	CTIONS:	Use typewriter or ball point pen	PLEASE PRESS FIRMLY	and PRINT clea	arly. Please fill in blan	ks and check the correct a	answers Send one conv to	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Toneka, Kansas 66612-1367								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html								