


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Ford	NE 1/4 NW 1/4 NW 1/4	22	T 28 S	R 24 EW

Distance and direction from nearest town or city street address of well if located within city?

From Dodge City, Ks. - Junction 156 & 283 6 miles South, 4 miles East on Ford-Ensign Road

2 WATER WELL OWNER:	Dean Dowling	Board of Agriculture, Division of Water Resources Application Number:
RR#, St. Address, Box # :	Route #3	
City, State, ZIP Code :	Dodge City, Kansas 67801	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 40.4 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL: 11.5 ft. below land surface measured on mo/day/yr 10-23-89
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield: 50 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 10 in. to 40.4 ft., and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes xx No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued x x x Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Other (specify below)
Blank casing diameter: 5 in. to 40.4 ft. Dia	5 in. to 40.4 ft. Dia	5 in. to 40.4 ft. Dia	5 in. to 40.4 ft. Dia
Casing height above land surface: 12 in.	weight: SDR 21	lbs./ft. Wall thickness or gauge No. 200 psi	
TYPE OF SCREEN OR PERFORATION MATERIAL: From 240 on down used 7 PVC 18 Asbestos-cement			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
GRAVEL PACK INTERVALS:			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other hole plug
Grout Intervals:	From 5 ft. to 40 ft.	From 5 ft. to 40 ft.	From 5 ft. to 40 ft.	From 5 ft. to 40 ft.
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? 75ft. Southeast				
How many feet?				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	Top soil & clay			
20	60	Clay			
60	80	Clay & fine sand (8 ft.)			
80	100	Fine sand			
100	140	Fine to medium sand (loose)			
140	270	Fine to medium sand w/small gravel			
270	280	Fine to medium sand w/small gravel			
280	290	Fine to medium sand			
290	300	Clay			
300	320	Clay layers & fine sand			
320	340	Fine to medium sand			
340	410	Fine to medium sand & small gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-26-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 11-10-89 under the business name of Joe's Well Service, Inc. Cimarron, Ks. by (signature) Judith Crist
