


USE TYPEWRITER OR BALL  
POINT PEN-PRESS FIRMLY,  
PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health  
(Water Well Contractors)  
Forbes-Bldg. 740  
Topeka, Kansas 66620

1 Location of well:	County <b>Ford</b>	Township name <b>Enterprise</b>	Fraction <b>SW 1/4 of SE 1/4</b>	Section number <b>29</b>	Town number <b>T-28-S</b>	Range number <b>R-24-W</b>																																																						
Distance and direction from nearest town or city: <b>10 mi. south and 3 east of Dodge City</b> Street address of well location if in city:				3 Owner of well: <b>George Scoggins</b> Address: <b>Dodge City, Kansas</b>																																																								
Locate with "X" in section below: 				Sketch map:																																																								
				4 Well depth: <b>296</b> ft. Date of completion <b>12-10-75</b> Well diameter <b>28</b> in.																																																								
				5 <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary																																																								
				6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well <input type="checkbox"/>																																																								
				7 Casing: Material <b>Metal</b> Height: above/below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface <b>12</b> in. Diam. <b>16</b> in. to <b>296</b> ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No _____ in. to _____ ft. depth																																																								
				8 Screen: Manufacturer <b>WA Brown</b> Type <b>Free-flo</b> Dia. <b>16</b> Slot/gauze <b>1/8</b> Length <b>2"</b> Set between <b>133</b> ft. and <b>293</b> ft. Fittings: Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material <b>GMA</b>																																																								
<table border="1"><thead><tr><th>Type and color of material</th><th>From</th><th>To</th></tr></thead><tbody><tr><td>Surface</td><td>0</td><td>3</td></tr><tr><td>Brown clay</td><td>3</td><td>130</td></tr><tr><td>Sand with 20% clay mixed</td><td>130</td><td>137</td></tr><tr><td>Brown clay</td><td>137</td><td>145</td></tr><tr><td>Med. sand</td><td>145</td><td>151</td></tr><tr><td>Brown clay</td><td>151</td><td>162</td></tr><tr><td>Sand and sandy clay</td><td>162</td><td>167</td></tr><tr><td>A-1 sand and gravel</td><td>167</td><td>180</td></tr><tr><td>Sand with 30% clay mixed</td><td>180</td><td>185</td></tr><tr><td>Good sand and gravel</td><td>185</td><td>195</td></tr><tr><td>Half med. sand with 20% clay mixed</td><td>195</td><td>200</td></tr><tr><td>Med. sand</td><td>200</td><td>203</td></tr><tr><td>Brown clay</td><td>203</td><td>220</td></tr><tr><td>A-1 fine to 1/2 med. sand and fine gravel</td><td>220</td><td>292</td></tr><tr><td>Brown clay</td><td>292</td><td>325</td></tr><tr><td>Yellow clay</td><td>325</td><td>345</td></tr><tr><td colspan="3">(use a second sheet if needed)</td></tr></tbody></table>				Type and color of material	From	To	Surface	0	3	Brown clay	3	130	Sand with 20% clay mixed	130	137	Brown clay	137	145	Med. sand	145	151	Brown clay	151	162	Sand and sandy clay	162	167	A-1 sand and gravel	167	180	Sand with 30% clay mixed	180	185	Good sand and gravel	185	195	Half med. sand with 20% clay mixed	195	200	Med. sand	200	203	Brown clay	203	220	A-1 fine to 1/2 med. sand and fine gravel	220	292	Brown clay	292	325	Yellow clay	325	345	(use a second sheet if needed)			9 Static water level: <b>121</b> ft. below land surface Date <b>11-12-75</b>		
				Type and color of material	From	To																																																						
				Surface	0	3																																																						
				Brown clay	3	130																																																						
				Sand with 20% clay mixed	130	137																																																						
				Brown clay	137	145																																																						
				Med. sand	145	151																																																						
				Brown clay	151	162																																																						
				Sand and sandy clay	162	167																																																						
				A-1 sand and gravel	167	180																																																						
Sand with 30% clay mixed	180	185																																																										
Good sand and gravel	185	195																																																										
Half med. sand with 20% clay mixed	195	200																																																										
Med. sand	200	203																																																										
Brown clay	203	220																																																										
A-1 fine to 1/2 med. sand and fine gravel	220	292																																																										
Brown clay	292	325																																																										
Yellow clay	325	345																																																										
(use a second sheet if needed)																																																												
10 Pumping level below land surfaces: <b>130</b> ft. after <b>2</b> hrs. pumping <b>675</b> g.p.m. <b>146</b> ft. after _____ hrs. pumping <b>1425</b> g.p.m. Estimated maximum yield <b>2500</b> g.p.m.																																																												
11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date _____																																																												
12 Well head completion: <input type="checkbox"/> Pitless adapter <input checked="" type="checkbox"/> Inches above grade																																																												
13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Depth: From <b>0</b> ft. to <b>10</b> ft.																																																												
14 Nearest source of possible contamination: <b>NA</b> ft. _____ Direction _____ Type _____ Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																																																												
15 Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name _____ Model number _____ HP _____ Volts _____ Length of drop pipe _____ ft. capacity _____ g.m.p. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																																												
16 Remarks: elevation  Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley				17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <b>Ace-Hi International Inc.</b> License No. <b>190</b> Business name <b>Dodge City, Kansas</b> Address <b>Dodge City, Kansas</b> Signed <b>Paul C. Smith</b> Date <b>12-10-75</b> Authorized representative																																																								

28 24 W 29 NW SW SE



**ACE-HI INTERNATIONAL, Inc.**

P.O. Box 1442

Dodge City, Kansas 67801

Phone: (316) 227-7306



12-17-75

Kansas Dept. of Health & Enviroment

This is to notify you thatthe following pump was installed  
in the well drilled by us for George Scoggins on section 29 T-28-S

R-24-W (Fred Co. Ks)  
Date installed 12-15-75

9 stage 10JHC Gould

200' of 8" drop pipe

80HP Amarillo gear drive

Designed for 700GPM at 80 PSI

Carl G. Mittel