WATER WELL RECORD Form WWC-5	Division of Water 30022			
✓ Original Record ☐ Correction ☐ Change in Well Use 1 LOCATION OF WATER WELL: Fraction	Resources App. No. Well ID Section Number Township Number Range Number			
County: Ford NE ¼ NE ¼ SW				
2 WELLOWNER: Last Name: Parker First: Kyle	Street or Rural Address where well is located (if unknown, distance and			
Business:	direction from nearest town or intersection): If at owner's address, check here:			
Address: 11864 113 Rd Address:	FROM SADDLE ROAD AND 114 INTERSECTION.			
City: Dodge City State: KS ZIP: 67801				
3 LOCATE WELL A DEPTH OF COMPLETED WELL	.: 360 ft. 5 Latitude: 37.628781 (decimal degrees)			
Doubles Constitution Engagement 1)	160 ft. (decimal degrees) Longitude: 99.956448 (decimal degrees)			
2) ft., or 4	Dry Well Datum: 7 WGS 84 NAD 83 NAD 27			
WELL'S STATIC WATER LEVEL:				
below land surface, measured on (moderate above land surface, measured on (moderate land surface, measured on (moderate land surface). ■				
above land surface, measured on (mo-d Pump test data: Well water was				
W after hours pumping	gpm			
Well water was				
after hours pumping Estimated Yield:800gpm	6 Elevation: ∠370ft. ✓ Ground Level ☐ TOC			
S Bore Hole Diameter:26 in. to36	O ⊕ and Source: ☐ Land Survey ☐ GPS ☐ Topographic Map			
mile in. to				
7 WELL WATER TO BE USED AS:	10 T O'I F' 11W +- C 1 - 1			
1. Domestic: 5. ☐ Public Water Supply: well ID 6. ☐ Dewatering: how many wells?				
☐ Lawn & Garden 7. ☐ Aquifer Recharge: well ID				
☐ Livestock 8. ☐ Monitoring: well ID	12. Geothermal: how many bores?			
2. ☑ Irrigation 9. Environmental Remediation: well ID				
3.				
Was a chemical/bacteriological sample submitted to KDHE?				
Water well disinfected? ✓ Yes ☐ No				
8 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other	CASING JOINTS: Glued Clamped Welded Threaded			
Casing diameter	in. to ft., Diameter in. to ft.			
Casing height above land surface	lbs./ft. Wall thickness or gauge No. SDR26			
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel ☐ PVC	Other (Specify)			
	e used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:				
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐	Torch Cut Drilled Holes Other (Specify)			
Louvered Shutter	Saw Cut			
GRAVEL PACK INTERVALS: From 30 ft. to 3	60 ft., From ft. to ft., From ft. to ft.			
9 GROUT MATERIAL: \(\text{Neat cement} \) \(\text{Cement grout} \) \(\text{\$\sqrt{Q}\$} \)	Bentonite			
Grout Intervals: From	ft. to ft., From ft. to ft.			
	contamination within 200 ft.			
□ Septic Tank □ Lateral Lines □ Pit Priv □ Sewer Lines □ Cess Pool □ Sewage				
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyar	d ☐ Fertilizer Storage ☐ Oil Well/Gas Well			
☐ Other (Specify) Direction from well? NW Distance from				
Direction from well? .INVV. Distance from 10 FROM TO LITHOLOGIC LOG				
Attached Attached Attached	FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS			
	Notes			
Notes:				
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged				
under my jurisdiction and was completed on (mo-day-year) .04/19/2019 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 846				
under the business name of Nash Water Well Service, LLC				
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.				
KS Department of Health and Environment, Bureau of Water, Geology Section Visit us at http://www.kdheks.gov/waterwell/index.html	, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565. KSA 82a-1212			

Form	WWC5	
Contractor	Nash Water Well Service, LLC	
Well Owner	Kyle Parker	
Doc ID	1443271	

Litholgy

Litt 1019 y		
0	36	TOP SOIL, TAN CLAY WITH
		FINE SAND STREAKS
36	110	FINE SAND WITH
		TAN CLAY STREAKS
110	120	FINE COARSE SAND WITH
		SMALL/MEDIUM GRAVEL STREAKS
120	160	FINE COARSE SAND WITH
		SMALL/LARGE GRAVEL
		AND LITTLE COBBLES
160	200	FINE COARSE SAND WITH
		TAN CLAY STREAKS
200	210	FINE COARSE SAND WITH
		SMALL GRAVEL STREAKS
210	245	FINE COARSE SAND
245	260	FINE MEDIUM SAND
260	280	TIGHT FINE SAND, TAN CLAY,
		TAN CALICHE
280	300	TAN CLAY WITH FINE SAND STREAKS
300	320	FINE SAND, TAN CLAY
320	325	BLUE/GRAY/YELLOW CLAY WITH FINE SAND
325	340	FINE SAND WITH TAN CLAY STREAKS

Form	WWC5	
Contractor	Nash Water Well Service, LLC	
Well Owner	Kyle Parker	
Doc ID	1443271	

Litholgy

340	1000	FINE MEDIUM SAND WITH TAN CLAY STREAKS
355	360	TIGHT, STICKY, TAN/BROWN CLAY