		WATER	WELL RECOR	D Earm M	\/\ <i>\</i> /^_=	KSA 82	a_1212		MW-3		
	VATER WELL:	Fraction		SE	Sec	tion Number	Township		R	ange Nu	ımber
County: Ford		MW SE ₄	NNX SE	1/4		XXXXX 1	L\$ ⊤28 \$2	X S	R	25	E/W
Distance and direct	tion from nearest town of south of Dodge	or city street add City	Iress of well if lo	ocated within	city?						
WATER WELL	OWNER: City of	f Dodge Ci	ty								
RR#, St. Address,		t. street						•	_		r Resources
City, State, ZIP Co		City, Kans						on Number:		N/A	
AN "X" IN SECT	N De	pth(s) Groundw	ater Encountere	ed 1	4	ft.	2	ft.	3 :	L-6-84	4ft.
	- NE Es	Pump t. Yield None	test data: Well	I water was I water was	None	e ft. a	urface measured of after	. hours p	oumping .		gpm
<u>*</u> w		ELL WATER TO				r supply			Injection		
. '		1 Domestic	3 Feedlot				9 Dewatering	•	•		pelow)
sw -	SE	2 Irrigation	4 Industria	l 7 Lawr	and g	arden only	10 Observation v	vell .			
	l sa Wa	as a chemical/ba	cteriological sar				/esNo				
4		tted		•			ater Well Disinfec			No	
TYPE OF BLAN	K CASING USED:		5 Wrought iron	8	Concre	ete tile	CASING J	OINTS: Glu	edx	. Clamp	ed
1 Steel	3 RMP (SR)		6 Asbestos-Cer	ment 9	Other ((specify belo	ow)	We	lded		
2_PVC	4 ABS		7 Fiberglass								
	eter 2 in.										
Casing height abov	e land surface24.		n., weight			Ibs	./ft. Wall thickness	or gauge	NoSc	hed.	40
TYPE OF SCREEN	OR PERFORATION M	MATERIAL:			7 PV	<u>C</u>	10 As	sbestos-cen	nent		
1 Steel	3 Stainless ste	eel	5 Fiberglass		8 RM	P (SR)	11 O	ther (specif	y) _.		
2 Brass	4 Galvanized	steel	6 Concrete tile		9 ABS	S	12 N	one used (d	pen hole)	
SCREEN OR PERI	FORATION OPENINGS	ARE:	5	Gauzed wrap	ped		8 Saw cut		11 No	ne (ope	n hole)
1 Continuous	slot 3 Mill s	lot	. 6	Wire wrapped	d		9 Drilled holes				ŕ
2 Louvered s	hutter 4 Key p			Torch cut			10 Other (spec	ify)			<i></i>
SCREEN-PERFOR	ATED INTERVALS:	From	ft.	to 1.24		ft., Fro	om	ft.	to		ft.
GRAVEL	PACK INTERVALS:	From 10	ft.	to 29			om 3.4				
-		From 129	11.	to 220		ft., Fro			to		ft.
GROUT MATER		ent 2	Cement grout	3	Bento		Other .Cemen				
Grout Intervals:	From	to	ft., From .	29	ft. ·	to34	ft., From .	129	ft. to	o134	ł
	t source of possible con					10 Live	stock pens		Abandon		well
 Septic tank 			7 Pit priv	⁄y			storage		Oil well/G		
2 Sewer lines	-		8 Sewag			12 Ferti	ilizer storage	16	Other (sp	ecify be	low)
-	sewer lines 6 Seepage	pit pit	9 Feedya	ard			cticide storage				
Direction from well							any feet? 3,	000	010 1 00		
FROM TO 10	Top soil	LITHOLOGIC L	JG		OM	TO		LITHOLO	GIC LOC	7	
10 20					50		Coarse sand				
20 30	Clay Clay			i	50		Coarse sand				
30 40	Clay				7.0		Ochre and S				
40 50			17.724	1	30		Dark Shale				
50 60	Clay Clay				00	_220	Dark Shale	3			
60 70	Clay		WARREN .								
70 80	•										
80 90	Sandy Clay Coarse sand		E-VIII.								
90 100	Coarse sand										
100 110	Coarse sand		· · ·						-		
110 120	Coarse sand										
120 130	Coarse sand										
130 140	Coarse sand										
140 150	Coarse sand										
		CEDTIEICATIO	Ni. This water	- /1\	onot	oted (0) ===	constructed or (a)	nlugged	nder mir	iuriodiati	on and was
CONTRACTOR	'S OR LANDOWNER'S day/year) Dec1	2 1082	in. This water v	veliwas (1) (onstruc	and this re-	ord is true to the 1	piugged ui	nowledge	and he	on and was p
										and be	4 4 5 5 5 7 1
	ctor's License No				ord wa			···/	97 . 94	, <u>,</u>	
	name of Weste Jse typewriter or ball poir sas Department of Health		PRESS FIRM	LY and PRIN		y. Please fill					
OWNER and retain	one for your records.	. and Environme	, DIVISION OF E				as comons roper	, 5002	Jona 0	10 10 117	