WATER WELL RECORD		Form W	WC-5		er Resources App. N		
1 LOCATION OF WATER WELL:		Fraction			Township No.		
County: Ford		½ SE ¼ SE	: ¼ SE ¼			R 25 DE XW	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:							
from nearest town or i	owner's address, check here .		Latitude: (in decimal degrees)				
From Dodge (ks South on H	W4 283			(in decimal degrees)		
·			Elevation: <u>Datum</u> : WGS 84, NAD 83, NAD 27				
2 WATER WELL OWNER: Michaison Jentures						J NAD 27	
RR#, Street Address,			Collection Method: GPS unit (Make/Model:)				
City State 7IP Code		7 Whirlwind Rd.		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Dodg	e (ity, Ks. 6)	7801		<3 m, ☐ 3-5 m, ☐		
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 365 ft.							
WITH AN "X" IN							
SECTION BOX:	Depth(s) Ground	lwater Encountered	(1)	ft. (2)	ft. ((3) ft.	
N	WELL'S STATIC WATER LEVEL						
	Pump test data: Well water wasft. after hours pumping gpm						
EST. YIELDgpm. Well water wasft. after hours pumpinggr						ping gpm	
W E Bore Hole Diameter 7.18 in. to 365 ft., and in. to ft.							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
Irrigation Industrial Domestic-lawn & garden Monitoring well							
was a chemical bacteriological sample submitted to Department?							
S If yes, mo/day/yr sample was submitted							
Water wen districted: 2 1cs 100							
5 TYPE OF CASING USED: Steel Y PVC Other							
CASING JOINTS: X Glued Clamped Welded Threaded							
Casing diameter							
Casing height above land surface							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From 285 ft. to 365 ft., From ft. to ft.							
From							
GRAVEL PACK INTERVALS: From							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From							
What is the nearest source of possible contamination:							
Septic tank							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well							
Direction from well				from well			
FROM TO	LITHOLOG		FROM			GGING INTERVALS	
	Clay	IC LOO	1 100101	LITHO. L	OO (cont.) OI FLU	COUNT INTERVALS	
	Clay Crock						
1			-				
110 120 med	1. Sand	-1	 				
130 140 Jan	Irock + Ta.	2 619					
	1 clay	1 1 -					
140 365 Mc	d. Sund to	19 197ers					
7 CONTRACTORS OF LANDOWNERS CERTIFICATION. This was a subject to the subject to t							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, plugged under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief							
Kansas Water Well Contractor's License No This Water Well Record was completed on (mo/day/year)							
under the business name of							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct asswers. Send three copies							
(white, blue, pink) to Kansas I	Department of Health	and Environment, Bureau	of Water, Geold	gy Section, 1000 SW Ja	ackson St., Saite 420,	Topeka, Kansas 66612-1367.	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212							