

1 LOCATION OF WATER WELL:		WATER WELL RECORD Form WWC-5 KSA 82a-1212			
County: FORD	Fraction NE 1/4 NE 1/4 NE 1/4	Section Number 15	Township Number T 28 S Range Number R 26 E/W		
Distance and direction from nearest town or city street address of well if located within city? 7 1/2 south and 7 west of Dodge City, Kansas					
2 WATER WELL OWNER:		Mr. LeRoy Reinert 2000 Burr Parkway Dodge City, Kansas 67801			
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Application Number: ----			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 180 ft. ELEVATION: Slope			
		Depth(s) Groundwater Encountered 1. Not available 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 160 ft. below land surface measured on mo/day/yr July 17, 1985			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 2 1/2 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 7/8 in. to 180 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No XX If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes XX No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued XX Clamped			
1 Steel 3 RMP (SR)		Welded			
XX PVC 4 ABS		Threaded			
5 Wrought iron 8 Concrete tile					
6 Asbestos-Cement 9 Other (specify below)					
7 Fiberglass					
Blank casing diameter 5 in. to 160 ft., Dia in. to ft.					
Casing height above land surface 24 in., weight 2.8 lbs./ft. Wall thickness or gauge No. 265					
TYPE OF SCREEN OR PERFORATION MATERIAL:		XX PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		XXS Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 160 ft. to 180 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 180 ft., From ft. to ft.					
6 GROUT MATERIAL: XX Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
XX Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? West		How many feet? 100			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0	2			Topsoil	
2	119			Clay	
119	153			Clay and Med. to Lar. Sand	
153	160			Fine Sand and Gravel	
160	172			Clay, Fine Sand and Gravel	
172	180			Caliche	
180	185			Black Shale	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) August 8, 1985 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/year) August 9, 1985 under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					