


1 LOCATION OF WATER WELL:		Fraction SW $\frac{1}{4}$ NW $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 26	Township Number T 28 S	Range Number R 28 EW
Distance and direction from nearest town or city street address of well if located within city? <i>4 1/4 miles east and 1/4 mile south of Montezuma.</i>					
2 WATER WELL OWNER:		Norval Johnson			
RR#, St. Address, Box #:		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code:		Application Number: <i>Cimarron, KS 67835</i>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL... 160' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 143' ft. below land surface measured on mo/day/yr 4-2-91 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 1/8 in. to 160' ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 6 Feedlot 9 Dewatering 12 Other (Specify below) 7 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No			
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel <input checked="" type="checkbox"/> PVC	8 Concrete tile 6 Asbestos-Cement 7 Fiberglass	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded	
Blank casing diameter		5' in. to 140' ft. Dia	in. to ft. Dia	in. to ft.	
Casing height above land surface		14 in., weight	lbs./ft. Wall thickness or gauge No. <i>SOR 21</i>	ft.	
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 2 Brass		3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
PVC					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)	
1 Continuous slot 2 Louvered shutter		3 Mill slot 4 Key punched	ft. to ft.	ft. to ft.	
SCREEN-PERFORATED INTERVALS:		From 140' ft. to 160' ft.	From ft. to ft.	ft. to ft.	
GRAVEL PACK INTERVALS:		From 20' ft. to 160' ft.	From ft. to ft.	ft. to ft.	
6 GROUT MATERIAL:		1 Neat cement Grout Intervals: From 0' ft. to 20' ft.	2 Cement grout From ft. to ft.	3 Bentonite 4 Other	ft. to ft.
What is the nearest source of possible contamination:					
1 Septic tank 2 Sewer lines 3 Watertight sewer lines		4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
Direction from well? <i>Every direction</i>					
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	20	<i>black topsoil Lt. brown clay</i>			
20	40	<i>Brown clay</i>			
40	60	<i>" "</i>			
60	80	<i>" "</i>			
80	100	<i>Brown clay + cliche layers</i>			
100	120	<i>" " Sand mixed</i>			
120	140	<i>Brown sandy clay - Med. Sand</i>			
140	160	<i>Med. Sand</i>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <i>4-2-91</i> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <i>533</i> This Water Well Record was completed on (mo/day/year) <i>4-2-91</i> under the business name of <i>Jantzen Water Well Repair</i> by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					