

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Gray, Fraction: SE 1/4 SE 1/4 NW 1/4, Section Number: 3, Township Number: T 28 S, Range Number: R 28 E, Distance and direction from nearest town or city street address of well if located within city? From Montezuma, 3 miles east on Hwy 56, then 1/2 miles north.

2 WATER WELL OWNER: Tony Kochr, RR#, St. Address, Box #: 25306 16 Rd., City, State, ZIP Code: Montezuma, KS. 67867, 3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with 'X' in NW corner], 4 DEPTH OF COMPLETED WELL: 413 ft., Depth(s) Groundwater Encountered, WELL'S STATIC WATER LEVEL: 320 ft. below land surface measured on mo/day/yr. 7/18/07.

5 TYPE OF CASING USED: 1 Steel, 3 RMP (SR), 6 Asbestos-Cement, 9 Other (specify below), 8 Concrete tile, CASING JOINTS: Glued, Clamped, Welded, Threaded, Blank casing diameter: 5 in. to 3.53 ft., Diameter, Casing height above land surface: 12 in., Weight, Wall thickness or gauge No. SDR 21, TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless Steel, 5 Fiberglass, PVC, 9 ABS, 11 Other (Specify), 2 Brass, 4 Galvanized Steel, 6 Concrete tile, 8 RM (SR), 10 Asbestos-Cement, 12 None used (open hole), SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 3 Mill slot, 5 Gauzed wrapped, 7 Torch cut, 9 Drilled holes, 11 None (open hole), 2 Louvered shutter, 4 Key punched, 6 Wire wrapped, Saw Cut, 10 Other (specify), SCREEN-PERFORATED INTERVALS: From 353 ft. to 413 ft., GRAVEL PACK INTERVALS: From 24 ft. to 413 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, Bentonite, 4 Other, Grout Intervals: From 4 ft. to 24 ft., What is the nearest source of possible contamination: 1 Septic tank, 4 Lateral lines, 7 Pit privy, 10 Livestock pens, 13 Insecticide Storage, 16 Other (specify), 2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 11 Fuel storage, 14 Abandoned water well below, 3 Watertight sewer lines, 6 Seepage pit, 9 Feedyard, 12 Fertilizer Storage, 15 Oil well/gas well nothing within 100'.

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-2 Topsoil, 2-12 Tan clay, 12-80 Fine sand, 80-125 Tan clay, 125-165 Tan sandy clay, 165-200 Tan clay & caliche, 200-220 Course sand, 220-240 Tan clay, 240-265 Med. sand, 265-290 Limestone & Tan clay.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/18/07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 533. This Water Well Record was completed on (mo/day/year) 11/31/08 under the business name of Jantzen Water well by (signature).

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.