


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Gray	Fraction SE 1/4 SE 1/4 SW 1/4	Section number 7	Township number T 28 S	Range number R 28 E
2. Distance and direction from nearest town or city: Street address of well location if in city:	From East side of Montezuma, KS go 1 1/4 N. 1/2 E. & N.		3. Owner of well: O. M. Fricke	R.R. or street: Box 224	
4. Locate with "X" in section below:	 Sketch map: 480' N. and 100' W. of SE corner of SW 1/4 of Sec. 7, T28S, R28W, Gray County, Kansas.		City, state, zip code: Montezuma, KS 67867	6. Bore hole dia. 28 in. Completion date 1-30-79 Well depth 455 ft.	
5. Type and color of material	From	To	7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
Top soil	0	3	9. Casing: Material St1 Height: Above or below <input type="checkbox"/> Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP PVC Weight 37 lbs./ft. Dia. 16 in. to 349 ft. depth Wall thickness: inches or Dia. 16 in. to 455 ft. depth Gage No. .219	10. Screen: Manufacturer's name Foster & Doerr Type M/S; Louver Dia. 16" Slot/gauze 1/16" Length 106' Set between 349 ft. and 455 ft. ft. and 455 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 2.25 mm	
Tan sandy clay with caliche streaks	3	142	11. Static water level: 206 ft. below land surface Date 10-9-78	12. Pumping level below land surfaces: 334 ft. after 1 hrs. pumping 1266 g.p.m. 334 ft. after 1 hrs. pumping 1300 g.p.m. Estimated maximum yield 1300 g.p.m.	
Fine to coarse sand and fine gravel	142	162	13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date	14. Well head completion: <input type="checkbox"/> Pitless adapter 12 Inches above grade	
Tan clay	162	190	15. Well grouted? <input checked="" type="checkbox"/> Yes With: <input type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.	16. Nearest source of possible contamination Unknown ft. 0 ft. Direction 0 Type 0 Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Limestone	190	214	17. Pump: Manufacturer's name Layne Not installed Model number 11BEH HP 123 Volts 110 Length of drop pipe 440 ft. capacity 1000 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	18. Elevation: Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley	
(Use a second sheet if needed)			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne-Western Co., Inc. 102 Business name Garden City, KS 67846 License No. 102 Address Garden City, KS 67846 Signed Layne Date 1-30-79 Authorized representative Layne		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5