

1 LOCATION OF WATER WELL: County: GRAY	Fraction NE 1/4 SW 1/4 NE 1/4	Section Number 24	Township Number T 28 S	Range Number R 29 E
--	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: EVAN'S TIRE & OIL RR#, St. Address, Box #: Hwy 56 City, State, ZIP Code: MONTEZUMA	Board of Agriculture, Division of Water Resources Application Number: MW 6
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 145 ft. ELEVATION: 2778.94 TOL
--	--

	Depth(s) Groundwater Encountered 1. 123.05 ft. 2. 145 ft. 3. 145 ft.
	WELL'S STATIC WATER LEVEL 123.05 ft. below land surface measured on mo/day/yr 3/12/93
	Pump test data: Well water was 778 gpm ft. after 778 hours pumping 778 gpm
	Est. Yield 778 gpm Well water was 778 ft. after 778 hours pumping 778 gpm
	Bore Hole Diameter 778 in. to 778 ft. and 778 in. to 778 ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted No	
Water Well Disinfected? Yes No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	
2 PVC 4 ABS 7 Fiberglass Threaded	
Blank casing diameter 4 in. to 114 ft. Dia 4 in. to 114 ft. Dia 4 in. to 114 ft.	
Casing height above land surface: Flush mount in. weight 4 lbs./ft. Wall thickness or gauge No. sch. 40	
TYPE OF SCREEN OR PERFORATION MATERIAL:	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes	
7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 114 ft. to 144 ft. From 114 ft. to 144 ft.	
GRAVEL PACK INTERVALS: From 55 ft. to 145 ft. From 55 ft. to 145 ft.	

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 2 ft. From 2 ft. to 53 ft. From 53 ft. to 55 ft.	
What is the nearest source of possible contamination:	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)	
Direction from well? How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	TOPSOIL			
3	5	CLAY, BR w/ SILT			
5	15	SILT, BR w/ CLAY			
15	25	SAND, FINE, BR, w/ SILT			
25	45	SILT, BR, w/ CLAY + CALCIE			
45	50	SILT, BR, FINE-MED SAND			
50	85	CLAY, BR, w/ SILT + MED SAND			
85	145	SAND, MED-COARSE, ARKOSTIC			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/13/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/yr) 4/20/93 under the business name of TEST by (signature) Charlie Harper
--