


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: GRAY	NE $\frac{1}{4}$ SW $\frac{1}{4}$ NE $\frac{1}{4}$	24	T 28 S	R 29 E

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER:	EVAN'S TIRE + OIL		Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Hwy 56		Application Number:
City, State, ZIP Code :	MONTEZUMA		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 145 ft. ELEVATION: 2778.67 TOC
	Depth(s) Groundwater Encountered 1.		ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 122.69 ft. below land surface measured on mo/day/yr		3/18/93
	Pump test data: Well water was ft. after hours pumping gpm		gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm		gpm
	Bore Hole Diameter 788 in. to ft., and in. to ft.		
	WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well		
	Was a chemical/bacteriological sample submitted to Department? Yes.....No.....		If yes, mo/day/yr sample was submitted
			Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	Welded
2 PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter 34 in. to 115 ft., Dia in. to ft., Dia in. to in. to ft.			
Casing height above land surface flush in., weight			lbs./ft. Wall thickness or gauge No. sch. 40
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 RMP (SR)	11 None (open hole)
1 Continuous slot 3 Mill slot	6 Wire wrapped	9 ABS	9 Drilled holes
2 Louvered shutter	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 120 to 145 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 55.5 to 145 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 to 46.91 ft., From 46.91 to 55.5 ft., From ft. to ft.				

What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well
1 Septic tank	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	13 Insecticide storage	
4 Lateral lines	How many feet?	
5 Cess pool		
6 Seepage pit		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	CLAY, BR			
3	5.5	CLAY, BR			
5.5	9	CLAY, BR			
9	13.5	SILT, GRAY, CLAY.			
13.5	15.0	" " " W/ SAND, FINE			
15	16	SAND, FINE-MED.			
16	18	SILTY, CLAY, FINE SAND			
18	31	SANDY SILT, FINE			
31	47	SILT, BR			
47	58	SILT, SAND, FINE			
58	60	SILTY, CLAY, GRAY			
60	70	SILT, BR			
70	90	SILTY SAND, FINE-MED			
90	146	SAND, ARKOSIC			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/18/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/yr) 4/20/93 by (signature) Mark Savage
--