## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction		Section	number	Township number	Range number		
1. Location of well:	Gray	SE1/4 SW1/4 NE 1/4		18		T 28 s	R 29	E_W_	
2. Distance and direction from nearest town or city: 2N, 4W, 2N, 4W 3. Owner				ner of well	ı. Ec	arl Fry (Victor		ヨ	
of Montezuma, Kansas R.R. or a Street address of well location if in city:						Montezuma, Kansas 67867			
City, sta				ate, zip code:		6. Bore hole dia. 28 in. Completion date			
4. Locate with "X" in section below:  N						Well depth 382 ft.	7-29-77		
810' E of the SW corner of						7 Cable tool Rotary	Driven _ Dug		
NE4, Sec. 18, T28S, R29W, Gr  NE4, Sec. 18, T28S, R29W, Gr  County, Kansas.					dy	Hollow rod Jetted			
						8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock			
						Lawn Oil field water Other			
						9. Casing: Material		v in.	
						RMP PVC	.  Weight37  lbs	./ft.	
1← 1 Mile → i				Ι		Dia. <u>16</u> n. to <u>150</u> r. depth Dia. <u>in.</u> to <u>ft. depth</u>		or	
5. Type and color of material				From	То	10 Savana Manufacturaris na	Foster.	$\exists$	
Top soil				0	8	Cook Doerr /w	3611	_	
						Type Millslot Slot/gauze 1/16	Dia		
Fine sand				8	45	Set betweenft. an-	t. and382	_ft.	
Tan sand	y clay			45	60	Gravel pack? X Size rang		<b>n</b>	
Tan clay				60	110	11. Static water level:	mo./day	у/уг. 77	
Fine to medium sand				110	115	12. Pumping level below land	surfaces.		
Fine to medium sand tight				115	125	220 ft. after 2 hrs 256 ft. after 1 hrs	s. pumping <u>1040</u> g.p s. pumping 1100g.p	o.m.	
Tine to	median said tight	·=				Estimated maximum yield		p.m.	
Fine to medium sand loose, clay streaks				125	136	13. Water sample submitted: Yes X No De	mo./day	y/yr.	
Tan clay and caliche				136	150	14. Well head completion:			
Fine to medium sand loose clay streaks				150	176		Inches above grad	e	
						15. Well grouted? X	Bentonite Conc	rete	Ŋ
Tan clay sand streaks				176	220	With: Neat 6ementX Depth: From ft. to	10 ft.		Þ
Fine to medium sand loose				220	252	16. Nearest source of possible			1
Tan clav	sand streaks			252	268	Well disinfected upon completi		_No	h
Fine sand loose				268		17. Pump:  Manufacturer's name Lay	Not installed	70	ע
			340		Model number 12KH	HP 125 Volts		1	
Tan clay			340	360	Length of drop pipe 300 Type:	. ft. capacity 1000p	.m.	(§	
Fine sand			360	382	Submersible	X Turbine		1	
Black shale (Use a second sheet if needed)			382	400	Jet Centrifugal	Reciprocati	ng s	1	
18. Elevation:	19. Remarks:			1	L	20. Water well contractor's ce		^ °	10
						This well was drilled under my	•	ort	r
Topography:						is true to the best of my knowled Layne-Western (		02 🕏	1
Hill						Business name Carden	City, Kanso	No.	16
Slope X Upland						Address // //	west.	4	18
Valley						Signed Authorized repre	sentative Aug	<b>₹</b>	:
Forward the white, blu	ue and pink copies to the Department	of Health and Environment					Form WWC-5		