

USE TYPEWRITER OR BALL  
POINT PEN-PRESS FIRMLY,  
PRINT CLEARLY.

WATER WELL RECORD  
KSA 82g-1201-1215

Kansas Department of Health and  
Environment-Division of Environment  
(Water well Contractors)  
Topeka, Kansas 66620

1. Location of well:	County Gray	Fraction NW 1/4 NE 1/4 NE 1/4	Section number 32	Township number T 28 S	Range number R 29
2. Distance and direction from nearest town or city:		3. Owner of well: David Toews			
Street address of well location if in city:		R.R. or street: City, state, zip code: Montezuma, Kansas 67867			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 12 in. Completion date _____ Well depth 206 ft. 2-03-77	
				7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary	
				8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
				9. Casing: Material PVC Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight 4.0 lbs./ft. Dia. 6 in. to 206 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 316	
5. Type and color of material		From	To	10. Screen: Manufacturer's name Jess & Lowell	
Top soil		0	5	Type PVC Dia. 6"	
Clay		5	12	Slot/gauge 1/8" Length 60'	
Fine sand		12	30	Set between 126 ft. and 206 ft.	
Fine sand with clay		30	74	ft. and ft. Gravel pack? Yes Size range of material #1 Fine	
Clay with some sand streaks		74	107	11. Static water level: mo./day/yr. 125 ft. below land surface Date 1/31/77	
Med. to lar. sand with clay streaks		107	170	12. Pumping level below land surfaces: 168 ft. after 1 hrs. pumping 20 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 26 g.p.m.	
Clay & med. to lar. sand (drilled loose)		170	210	13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No Date	
				14. Well head completion: <input checked="" type="checkbox"/> Pitless <del>adaptor</del> Unit Inches above grade	
				15. Well grouted? Yes With: Neat cement Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 4 ft. to 14 ft.	
				16. Nearest source of possible contamination: ft. 250 Direction SW Type old well Well disinfected upon completion? <input checked="" type="checkbox"/> Yes No	
				17. Pump: Not installed Manufacturer's name Aermotor Model number SD19 HP 1 1/2 Volts 220 Length of drop pipe 189 ft. capacity 20 g.p.m. Type: <input checked="" type="checkbox"/> Submersible Turbine <input type="checkbox"/> Jet Reciprocating <input type="checkbox"/> Centrifugal Other	
(Use a second sheet if needed)					
18. Elevation:	19. Remarks:				
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley					
20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <b>Friesen Windmill</b> 252 Business name <b>Meade, Kansas</b> License No. Address 67864 Signed <b>John Friesen</b> Date 3-2-77 Authorized representative					

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5