

17960449

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4

1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 SE 1/4 Section Number 25 Township Number T 28 S Range Number R 3 E
 County: Sedgwick Distance and direction from nearest town or city street address of well if located within city? See Below

2 WATER WELL OWNER: DAVE GOODRICH Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: 2200 N. 6th St Application Number:
 City, State, ZIP Code: Viola, KS

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N							
W	<table border="1"> <tr> <td>NW</td> <td>NE</td> </tr> <tr> <td>SW</td> <td>SE</td> </tr> </table>	NW	NE	SW	SE	E	
NW	NE						
SW	SE						
S							

4 DEPTH OF COMPLETED WELL: 13 ft. ELEVATION: 11/22/95
 Depth(s) Groundwater Encountered 9.5 ft. 2. 13 ft. 3. 11/22/95
 WELL'S STATIC WATER LEVEL 9.5 ft. below land surface measured on mo/day/yr 11/22/95
 Pump test data: Well water was 30 ft. after 11 hours pumping 160 gpm
 Est. Yield 30 gpm Well water was 160 ft. after 11 hours pumping 160 gpm
 Bore Hole Diameter 11 in. to 160 ft. and 160 in. to 160 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X
 2 PVC 4 ABS 7 Fiberglass Threaded X
 Blank casing diameter 12 in. to 20 ft. Dia 2.160 in. to 160 ft. Dia 160 PSI
 Casing height above land surface 12 in., weight 2.160 lbs./ft. Wall thickness or gauge No. 160 PSI
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 2 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 20 ft. to 60 ft. From 13 ft. to 160 ft.
 GRAVEL PACK INTERVALS: From 13 ft. to 160 ft. From 13 ft. to 160 ft.

6 GROUT MATERIAL: 3 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 13 ft. From 13 ft. to 160 ft. From 13 ft. to 160 ft. From 13 ft. to 160 ft.
 What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? Southwest How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	11	clay			
11	26	sand			
26	60	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/22/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 11/22/95
 under the business name of Weninger Drilling by (signature) Karrina D. Brann