


1 LOCATION OF WATER WELL: *		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SE 1/4 NE 1/4 NE 1/4	22	T 28 S	R 3 E 10
Distance and direction from nearest town or city street address of well if located within city? Rt 1, Lake Afton, Goddard					
2 WATER WELL OWNER: BDAT		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 1862 Craigshire		Application Number:			
City, State, ZIP Code: St. Louis, MO 63146					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 21 ft. ELEVATION: 1376.87'			
N W E S 		Depth(s) Groundwater Encountered 1. 16 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 17.5 ft. below land surface measured on mo/day/yr 9-29-95			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 21 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well MW-4			
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was sub- mitted			
		Water Well Disinfected? Yes No ☒			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped Welded Threaded ☒			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter in. to ft. Dia in. to ft. Dia in. to ft.		7 Fiberglass			
Casing height above land surface Flush in. weight lbs./ft. Wall thickness or gauge No. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot		6 Wire wrapped 9 Drilled holes			
2 Louvered shutter 4 Key punched		7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 11 ft. to 21 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 8 ft. to 21 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 1.5 ft. From 1.5 ft. to 8 ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet? 0			
Direction from well?					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0 3 Silty Clay					
3 16 UST basin backfill					
16 17 Silty Clay					
17 21 Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-28-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 571 This Water Well Record was completed on (mo/day/yr) 1-15-96 under the business name of BDAT by (signature) Boyle					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4