

1] LOCATION OF WATER WELL: County: Seagov NE 1/4 NE 1/4 SW 1/4 Section Number 23 Township Number 280 Range Number 3 W

Distance and direction from nearest town or city street address of well if located within city? #8 Lake Ridge - Goddard "Lk. Walters"

2] WATER WELL OWNER: Glenda meyerden Board of Agriculture, Division of Water Resources

RR#, St. Address, Box #: 1000 w. prairie Application Number:

City, State, ZIP Code: Wichita, KS 67209

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4] DEPTH OF COMPLETED WELL: 101 ft. ELEVATION: 5-1401 ft.

Depth(s) Groundwater Encountered: 32 ft. below land surface measured on mo/day/yr

WELL'S STATIC WATER LEVEL: 32 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 20 gpm. Well water was 101 ft. after 11 hours pumping 101 gpm.

Est. Yield 20 gpm. Well water was 101 ft. after 11 hours pumping 101 gpm.

Bore Hole Diameter: 11 in. to 101 ft., and 101 in. to 101 ft.

WELL WATER TO BE USED AS:

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was sub

5] TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter: 5 in. Dia. 81 in. Dia. 2.40 in. Dia. 160psi ft.

Casing height above land surface: 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160psi

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 PVC 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 01 ft. to 101 ft. From 01 ft. to 101 ft.

GRAVEL PACK INTERVALS: From 32 ft. to 101 ft. From 32 ft. to 101 ft.

6] GROUT MATERIAL: 1 Neat cement 320 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 32 ft. to 320 ft. From 32 ft. to 320 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage 90

Direction from well? north-east How many feet? 90

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 18 clay

18 36 fine to med sand

36 101 shale

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-14-01 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 380 This Water Well Record was completed on (mo/day/yr) 5-20-01

under the business name of Weninger Drilling Inc. by (signature) Michael G. G. G.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.