

1 LOCATION OF WATER WELL: County: Sedgwick Section Number: 28 Township Number: 28 Range Number: 3 Distance and direction from nearest town or city street address of well if located within city? 263rd W & 63rd S. - 1/4 NE, 1/4 W.

2 WATER WELL OWNER: Denise Vaughn Board of Agriculture, Division of Water Resources Application Number: 5-2301

RR#, St. Address, Box #: 1803 N. Holland City, State, ZIP Code: Wichita, KS 67212

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 

4 DEPTH OF COMPLETED WELL: 77 ft. ELEVATION: 5-2301 ft. Depth(s) Groundwater Encountered: 10 ft. below land surface measured on mo/day/yr. WELL'S STATIC WATER LEVEL: 10 ft. below land surface measured on mo/day/yr. Pump test data: Well water was 22 gpm. Well water was 77 ft. after 11 hours pumping 11 gpm. Est. Yield: 22 gpm. Well water was 77 ft. after 11 hours pumping 11 gpm. Bore Hole Diameter: 11 in. to 77 ft. and 11 in. to 77 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 12 Other (Specify below) 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 10 Monitoring well 2 Irrigation 4 Industrial 7 Lawn and garden only

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Threaded X Blank casing diameter: 5 in. to 17 ft. Dia. 2.40 in. to 160 psi lbs./ft. Wall thickness or gauge No. Casing height above land surface: 12 in. weight 2.40 lbs./ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 17 ft. to 77 ft. From 10 ft. to 77 ft. GRAVEL PACK INTERVALS: From 10 ft. to 77 ft. From 10 ft. to 77 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 10 ft. From 10 ft. to 77 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Open field 13 Insecticide storage

Direction from well? Open field How many feet? Open field

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-2301 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 308 This Water Well Record was completed on (mo/day/yr) 5-31-01 under the business name of Weninger Drilling Inc. by (signature) Michael G. Gorge

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 785-296-5545. Send one to WATER WELL OWNER and retain one for your records.