

1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NE 1/4 Section Number 11 Township Number 28S Range Number 30E
County: Sedgwick
Distance and direction from nearest town or city street address of well if located within city: 3215 S. 23rd St. W.

2 WATER WELL OWNER: Elmer & Joann Koelings
RR#, St. Address, Box #: 600
City, State, ZIP Code: Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
N
NW NE
SW SE
S

4 DEPTH OF COMPLETED WELL 60 ft. ELEVATION: 8-4-04 ft.
Depth(s) Groundwater Encountered: 15 ft. 2 ft. 3 ft.
WELL'S STATIC WATER LEVEL: 15 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 25 gpm: Well water was 25 ft. after 25 hours pumping 25 gpm
Est. Yield 25 gpm: Well water was 25 ft. after 25 hours pumping 25 gpm
WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Domestic (lawn & garden) 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded
Blank casing diameter 5 in. to 33 ft. Dia 12 in. to 2.40 in. Dia 100 psi
Casing height above land surface 12 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 100 psi
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 33 ft. to 60 ft. From 15 ft. to 60 ft. From 60 ft. to 60 ft. From 60 ft. to 60 ft.
GRAVEL PACK INTERVALS: From 15 ft. to 60 ft. From 60 ft. to 60 ft. From 60 ft. to 60 ft. From 60 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 15 ft. From 15 ft. to 60 ft. From 60 ft. to 60 ft. From 60 ft. to 60 ft.
What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Sepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
Direction from well? Northeast How many feet? 100

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-11-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/yr) 8-11-04 under the business name of Wellinger Drilling Inc. by (signature) D. Wellinger

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.