_		WATER WELL RECORD	Form WWC-5	KSA 82a	-1212		
LOCATION OF WA	TER WELL: Frac	tion	Sect	ion Number	Township Number	Range Number	
County: Sedawic			1/4	1	т 28 s	R 3W E/W)	
Distance and direction	n from nearest town or city	street address of well if locate	ed within city?				
2421 S. 222 2 WATER WELL OV		, KS.					
	" I aranomic	Homes: Mark Delma	וב		Board of Agriculture	Division of Water Resources	
RR#, St. Address, Bo	2020 11000					Division of water Resources	
City, State, ZIP Code	**************************************				Application Number:		
AN "X" IN SECTIO	Depth(s)	H OF COMPLETED WELL Groundwater Encountered	<u>1.</u> 27	ft. 2	2 ft.	3	
ī!	WELL'S	STATIC WATER LEVEL 2	ft. be	elow land sur	face measured on mo/day/y	·3 10 . -89	
NW	NE	Pump test data: Well wat	ter was	ft. a	fter hours p	umping gpm	
	Est. Yield	d gpm: Well wat	er was	ft. a	fter hours p	umping gpm	
	Bore Hol	e Diameter11in. to)		and	n. to	
W I		ATER TO BE USED AS:	5 Public water			Injection well	
- i	1 1 1	omestic 3 Feedlot			9 Dewatering 12	•	
SW	SE						
] 1		igation 4 Industrial nemical/bacteriological sample	/ Lawn and g	arden only	10 Monitoring wellX		
ļ <u> </u>		nemical/bacteriological sample	submitted to De				
-	<u>s</u> mitted				ter Well Disinfected? Yes	17	
TYPE OF BLANK	CASING USED:	5 Wrought iron	8 Concre			nd Clamped	
1 Steel	3_RMP_(SR)	6 Asbestos-Cement	9 Other (specify below		jed	
2 PVC	4 ABS	7 Fiberglass	Cer-Ma	c. styren	t SDR-26 Thre	aded	
Blank casing diamete	r in. to	40 ft., Dia	in. to		ft., Dia	in. to ft.	
Casing height above	land surface. 12	in., weight1.5	59	Ibs./	ft. Wall thickness or gauge f	_{lo.} •203	
	OR PERFORATION MATER		7 PV0		10 Asbestos-cem		
				-			
	1 Steel 3 Stainless steel				(SR) 11 Other (specify)		
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	•	12 None used (o		
SCREEN OR PERFO	PRATION OPENINGS ARE:		zed wrapped		8 Saw cut	11 None (open hole)	
1 Continuous sl	ot 3 Mill slot	6 Wire	wrapped		9 Drilled holes		
2 Louvered shu	tter 4 Key punche						
SCREEN-PERFORAT	TED INTERVALS: From	<u>4</u> 0 ft. to .		ft., Froi	n ft.	toft.	
	From	ft. to .		ft., Fro	m ft.	toft.	
GRAVEL PA		24 ft. to .					
G. W.V.E.E. F.	From						
COOLT MATERIA		2 Cement grout			Other		
6 GROUT MATERIA							
		.24 ft., From	π. ι				
What is the nearest s	ource of possible contamination				F	Abandoned water well	
 Septic tank 	4 Lateral lines	7 Pit privy		11 Fuel	storage 15 (Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lag	8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)		
3 Watertight sev	wer lines 6 Seepage pit	9 Feedyard		13 insec	ticide storage None Ap	parent	
Direction from well?				How ma	nv feet?		
FROM TO	LITHO	LOGIC LOG	FROM	ТО	PLUGGING	INTERVALS	
0 3 -	topsoil						
	1 -						
3 39	clay		+				
39 50	fine sand		+	-			
50 60	grey shale		1				
	<u> </u>						
			+				
			. 1				
			- 				
		TFICATION: This water well was a second of the second of t					
completed on (mo/day	y/year) 3 –1 0–8	39		and this reco	rd is true to the best of my ki	nowledge and belief. Kansas	
completed on (mo/day	y/year) 3 –1 0–8	39		and this reco	rd is true to the best of my ki on (mo/day/yr)	nowledge and belief. Kansas	
completed on (mo/day Water Well Contracto	y/year)		Well Record was	and this reco	rd is true to the best of my ki on (mo/day/yr)	nowledge and belief. Kansas	