

[1] LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SW ¼ NW ¼ NE ¼	15	T 28 S	R 3 W EW
Distance and direction from nearest town or city street address of well if located within city?					
Southeast of MacArthur and the Viola Rd., Lake Afton, Goddard, Ks.					
[2]	WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Sedgwick County Purchasing Dept. 525 N. Main Wichita, Ks.		
		Board of Agriculture, Division of Water Resources Application Number:			
[3]	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		[4]	DEPTH OF COMPLETED WELL.....115 ft. ELEVATION:	
N W E S		Depth(s) Groundwater Encountered 1.....17 ft. 2..... ft. 3..... ft. WELL'S STATIC WATER LEVEL17 ft. below land surface measured on mo/day/yr 4-19-82 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>7 Lawn and garden only</u> 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No...X.... If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
		TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter5 in. to20 ft., Dia Cer-Mac Styrene SDR-26 Casing height above land surface12 in., weight1.59 lbs./ft. Wall thickness or gauge No.203 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 2 Torch cut 10 Other (specify)			
		SCREEN-PERFORATED INTERVALS: From20 ft. to115 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From14 ft. to115 ft., From ft. to ft. From ft. to ft., From ft. to ft.			
		[6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From4 ft. to14 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? Southeast How many feet? 65			
FROM TO		LITHOLOGIC LOG	FROM TO		LITHOLOGIC LOG
0	3	Topsoil			
3	52	Red Shale			
52	115	Grey Shale			
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-19-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 6-17-82 under the business name of Harp Well & Pump Serv., Inc. by (signature) M. Arnold					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					