

1 LOCATION OF WATER WELL: County: <u>Sedgewick</u>		Fraction <u>SE</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	Section Number <u>15</u>	Township Number T <u>28</u> S	Range Number R <u>3</u> E <u>(W)</u>
---	--	---	-----------------------------	----------------------------------	---

Distance and direction from nearest town or city street address of well if located within city?

N 27 LAKE WALTANNA-BEAVER CREEK CT - GODDARD, KS

2 WATER WELL OWNER: Wesley Jones
 RR#, St. Address, Box # : 1834 W. Rest Wick
 City, State, ZIP Code : Wichita, KS 67212

Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 0000 ft. ELEVATION: 0000

Depth(s) Groundwater Encountered 1. 38 ft. 2. 75 ft. 3. 11-20-87 ft.

WELL'S STATIC WATER LEVEL 38 ft. below land surface measured on mo/day/yr 11-20-87

Pump test data: Well water was 75 ft. after 1/2 hours pumping 10 gpm

Est. Yield 10-15 gpm: Well water was 75 ft. after 1/2 hours pumping 10 gpm

Bore Hole Diameter 11 in. to 80 ft., and 11 in. to 80 ft.

WELL WATER TO BE USED AS:

<u>1</u> Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	11 Injection well
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Observation well	12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted 11-20-87

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☐
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded ☐
2 PVC 4 ABS 7 Fiberglass Threaded ☐
Blank casing diameter 5 in. to 80 ft. Dia. in. to ft. Dia. in. to ft.
Casing height above land surface 12 in. weight 159 lbs./ft. Wall thickness or gauge No. SPR-26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 28 ft. to 80 ft., From ft. to ft.
From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 23 ft. to 80 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
13 Insecticide storage				

Direction from well? EAST

How many feet? 60

Direction from well? EAST How many feet? 60

[illegible]

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/20/1987 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 3680 This Water Well Record was completed on (mo/day/yr) 11/23/1987 under the business name of Wm. J. Water Drilling Co. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. **PLEASE PRESS FIRMLY and PRINT** clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to **WATER WELL OWNER** and retain one for your records.