

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NW 1/4 SW 1/4 NW 1/4	18	T 28 S	R 3 E/W
Distance and direction from nearest town or city street address of well if located within city? See Below					
2 WATER WELL OWNER: Steve Escareno					
RR#, St. Address, Box #: 4160 S. 311 West					
City, State, ZIP Code: Garden Plain KS 67050					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 ft. 2. ft. 3. 8-28-92 ft.			
		WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		☐ Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes ☒ No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
Blank casing diameter 5 in. to 20 ft. Dia		7 Fiberglass		8 Concrete tile	
Casing height above land surface 12 in. weight 760 lbs./ft. Wall thickness or gauge No. 160PVC		8 RMP (SR)		9 Other (specify below)	
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement		CASING JOINTS: Glued ☒ Clamped	
1 Steel		3 Stainless steel		Welded	
2 Brass		4 Galvanized steel		Threaded	
SCREEN OR PERFORATION OPENINGS ARE:		5 Fiberglass		11 Other (specify)	
1 Continuous slot		6 Concrete tile		12 None used (open hole)	
2 Louvered shutter		7 Torch cut		8 Saw cut	
3 Mill slot		8 RMP (SR)		11 None (open hole)	
4 Key punched		9 ABS		9 Drilled holes	
SCREEN-PERFORATED INTERVALS:		5 Gauzed wrapped		10 Other (specify)	
From 20 ft. to 80 ft.		6 Wire wrapped			
GRAVEL PACK INTERVALS:		7 Torched			
From 20 ft. to 80 ft.		8 Saw cut			
		9 Drilled holes			
		10 Other (specify)			
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
Grout Intervals: From 3 ft. to 20 ft.		4 Other			
What is the nearest source of possible contamination:		5 Gauzed wrapped		8 Saw cut	
1 Septic tank		6 Wire wrapped		11 None (open hole)	
2 Sewer lines		7 Torched		9 Drilled holes	
3 Watertight sewer lines		8 Saw cut		10 Other (specify)	
4 Lateral lines		9 Drilled holes			
5 Cess pool		10 Other (specify)			
6 Seepage pit					
7 Pit privy					
8 Sewage lagoon					
9 Feedyard					
10 Livestock pens					
11 Fuel storage					
12 Fertilizer storage					
13 Insecticide storage					
14 Abandoned water well					
15 Oil well/Gas well					
16 Other (specify below)					
Direction from well? EAST		How many feet? 120			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	6	clay			
6	9	sand			
9	80	shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-28-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 8-31-92 under the business name of Weninger Drilling Inc by (signature) Susan Weninger					