

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

Billed to: Ray Katzenmiller

1. Location of well:		County: <u>Sedgewick</u>	Fraction: <u>1/4 NE 1/4 SW 1/4</u>	Section number: <u>23</u>	Township number: <u>28</u>	Range number: <u>3</u>
2. Distance and direction from nearest town or city:		3. Owner of well: <u>Midwest Realty Constr</u>		R.R. or street: <u>3202 W. 13th</u>		
Street address of well location if in city: <u>Challenger Lake Matanzas</u>		City, state, zip code: <u>Wichita, Kansas</u>				
4. Locate with "X" in section below:		Sketch map: <u>Goddard, Kansas</u>		6. Bore hole dia. <u>125</u> in. Completion date <u>3-30-76</u>		
				Well depth <u>125</u> ft.		
				7. Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐		
				☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary		
				8. Use: ☐ Domestic ☐ Public supply ☐ Industry		
				☐ Irrigation ☐ Air conditioning ☐ Stock		
				☐ Lawn ☐ Oil field water ☐ Other		
				9. Casing: Material <u>STYRENE</u> Above or below		
				Threaded ☐ Welded ☒ Surface <u>12</u> in.		
				RMP ☒ PVC ☐ Weight <u>125</u> lbs./ft.		
				Dia. <u>5</u> in. to <u>125</u> ft. depth Wall Thickness: inches <u>1.200</u>		
				Dia. <u>5</u> in. to <u>125</u> ft. depth gage No. <u>1.200</u>		
5. Type and color of material		From	To	10. Screen Manufacturer's name <u>SUNFLOWER PLASTIC</u>		
<u>Topsoil</u>		<u>0</u>	<u>2</u>	Type <u>STYRENE</u> Dia. <u>3"</u>		
<u>Sandy Clay</u>		<u>2</u>	<u>8</u>	Slot/gauze <u>106</u> Length <u>95</u>		
<u>Fine Sand with Clay ball</u>		<u>8</u>	<u>20</u>	Set between <u>30</u> ft. and <u>125</u> ft.		
<u>Blue Shale</u>		<u>20</u>	<u>80</u>	Gravel pack? <u>YES</u> Size range of material <u>44-18"</u>		
<u>Red Shale</u>		<u>80</u>	<u>90</u>	11. Static water level: <u>25</u> ft. below land surface Date <u>3-30-76</u>		
<u>Blue Shale</u>		<u>90</u>	<u>125</u>	12. Pumping level below land surfaces:		
				<u>25</u> ft. after <u>12</u> hrs. pumping <u>230</u> g.p.m.		
				<u>25</u> ft. after <u>12</u> hrs. pumping <u>230</u> g.p.m.		
				Estimated maximum yield <u>230</u> g.p.m.		
				13. Water sample submitted: <u>NO</u> mo./day/yr.		
				Yes ☐ No ☒ Date <u>3-30-76</u>		
				14. Well head completion: <u>X</u> Pitless adapter <u>12</u> inches above grade		
				15. Well grouted? <u>YES</u>		
				With: <u>Neat cement</u> ☐ <u>Bestonite</u> ☒ <u>Concrete</u> ☐		
				Depth: From <u>40'</u> to <u>14'</u> ft.		
				16. Nearest source of possible contamination: <u>Septic tank</u>		
				ft. <u>60</u> Direction <u>NW</u> Type <u>Septic tank</u>		
				Well disinfected upon completion? ☒ Yes ☐ No		
				17. Pump: <u>Not installed</u>		
				Manufacturer's name <u>Rite</u>		
				Model number <u>1P6D2</u> HP <u>3/4</u> Volts <u>230</u>		
				Length of drop pipe <u>100</u> ft. capacity <u>20</u> g.p.m.		
				Type: ☒ Submersible ☐ Turbine		
				☐ Jet ☐ Reciprocating		
				☐ Centrifugal ☐ Other		
18. Elevation:		(Use a second sheet if needed)		20. Water well contractor's certification:		
Topography: <u>Flat Ground</u>				This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
				<u>HARP WELL-PUMP</u> <u>236</u>		
				Business name <u>WICHITA, KANSAS</u> License No. <u>236</u>		
				Address <u>WICHITA, KANSAS</u>		
				Signed <u>M. Arnold</u> Date <u>3-30-76</u>		
				Authorized representative <u>3-30-76</u>		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5