

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedg.</u>		<u>SE 1/4 SE 1/4 SW 1/4</u>	<u>31</u>	T <u>28</u> S	R <u>3</u> EW <u>0</u>
Distance and direction from nearest town or city street address of well if located within city? <u>See Below</u>					
2 WATER WELL OWNER: <u>DAK Rausch</u>					
RR#, St. Address, Box # : <u>30540 W. 7th St</u>					
City, State, ZIP Code : <u>Cheney KS 67025</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>28</u> ft. ELEVATION: <u>28</u> ft.			
		Depth(s) Groundwater Encountered 1. <u>18</u> ft. 2. <u>18</u> ft. 3. <u>18</u> ft.			
		WELL'S STATIC WATER LEVEL <u>18</u> ft. below land surface measured on mo/day/yr <u>10-15-93</u>			
		Pump test data: Well water was <u>20</u> ft. after <u>12</u> hours pumping <u>26</u> gpm			
		Est. Yield <u>30</u> gpm: Well water was <u>28</u> ft. after <u>12</u> hours pumping <u>26</u> gpm			
		Bore Hole Diameter <u>11</u> in. to <u>28</u> ft., and <u>28</u> in. to <u>28</u> ft.			
		WELL WATER TO BE USED AS:			
		☒ 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ☐ 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>X</u> No <u>X</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped ☒ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>5</u> in. to <u>18</u> ft. Dia. <u>2</u> in. to <u>60</u> lbs./ft. Wall thickness or gauge No. <u>160 PVC</u> Casing height above land surface <u>12</u> in., weight <u>2</u> lbs./ft.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ☒ 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From <u>18</u> ft. to <u>28</u> ft. From <u>18</u> ft. to <u>28</u> ft. GRAVEL PACK INTERVALS: From <u>18</u> ft. to <u>28</u> ft. From <u>18</u> ft. to <u>28</u> ft.					
6 GROUT MATERIAL: 1 Neat cement ☒ 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>18</u> ft. From <u>18</u> ft. to <u>28</u> ft. From <u>28</u> ft. to <u>28</u> ft.					
What is the nearest source of possible contamination:					
☒ 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? <u>So</u> How many feet? <u>100</u>					
FROM		TO		LITHOLOGIC LOG	
FROM		TO		PLUGGING INTERVALS	
0		2		Top soil	
2		13		Clay	
13		24		fine to med sand	
24		28		Red shale	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, ☐ (2) reconstructed, or ☐ (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-15-93</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>11-10-93</u> under the business name of <u>Wenger Dilling</u> by (signature) <u>Wenger</u>					