

1 LOCATION OF WATER WELL: County: Sedawick		Fraction: NE 1/4 NW 1/4 NE 1/4	Section Number: 1	Township Number: 28	Range Number: 3
Distance and direction from nearest town or city street address of well if located within city? See Below					
2 WATER WELL OWNER: Brian Hahn					
RR#, St. Address, Box #: 22601 W. 23rd St.				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: Goddard KS 67052				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 64 ft. ELEVATION:			
		Depth(s) Groundwater Encountered: 1. 44 ft. 2. 44 ft. 3. 1-26-95 ft.			
		WELL'S STATIC WATER LEVEL: 44 ft. below land surface measured on mo/day/yr 1-26-95			
		Pump test data: Well water was 30 gpm. Well water was 44 ft. after 1/2 hours pumping 30 gpm			
		Est. Yield: 30 gpm. Well water was 64 ft. after 1/2 hours pumping 30 gpm			
Bore Hole Diameter: 11 in. to 64 ft., and 11 in. to 64 ft.		WELL WATER TO BE USED AS:			
1 Domestic		3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation		4 Industrial	7 Lawn and garden only	10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No ☒					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped ☒
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded ☒
Blank casing diameter: 5 in. to 52 ft., Dia 12 in. to 2.60 in. to 160 PSI		7 Fiberglass	Threaded ☒		
Casing height above land surface: 12 in., weight 2.60 lbs./ft. Wall thickness or gauge No. 160 PSI		TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From 52 ft. to 64 ft.	From 64 ft. to 64 ft.	From 64 ft. to 64 ft.	From 64 ft. to 64 ft.
GRAVEL PACK INTERVALS:		From 40 ft. to 64 ft.	From 64 ft. to 64 ft.	From 64 ft. to 64 ft.	From 64 ft. to 64 ft.
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 3 ft. to 15 ft.		From 15 ft. to 64 ft.	From 64 ft. to 64 ft.	From 64 ft. to 64 ft.	From 64 ft. to 64 ft.
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? South east		How many feet? 180			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	45	clay			
45	60	medium sand			
60	64	red shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-26-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 2-6-95 under the business name of Weninger Drilling, Inc. by (signature) Karina Morrissey					