WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: County: Lyngman	Fraction 1/4 SE1/4SE 1/4SE1/4	Section Number Township No. Range Number T 2 S R S DE W
Street/Rural Address of Well Location	; if unknown, distance & direction	Global Positioning System (GPS) information:
from nearest town or intersection: If a		Latitude: (in decimal degrees)
2/2 W. Kingman	3N.	Longitude: (in decimal degrees) Elevation:
P		Datum: WGS 84, NAD 83, NAD 27
2 WATER WELL OWNER: RR#, Street Address, Box #: City, State, ZIP Code :	55 KINSLEY	Collection Method:
RR#, Street Address, Box #:	2746 NW 30	GPS unit (Make/Model:)
City, State, ZIP Code :	gman, KS 6-7068	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
3 LOCATE WELL	grady and a resident	CIV
WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL	ft.
SECTION BOX: Depth(s) Groun	ndwater Encountered (1)	ft. (2) ft. (3) ft.
SECTION BOX: N Depth(s) Groundwater Encountered (1)		
EST. YIELD.	Legon Well water was	ft. after hours pumping gpm
W - NW NE - EST. HELD	meter	ft. after hours pumping gpm t., andft.
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well		
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)		
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well		
s If yes, mo/day/yr sample was submitted		
Water well disinfected? Yes \[\] No		
5 TYPE OF CASING USED: Steel PVC Other		
CASING IOINTS: A Glued C Clamped C Welded C Threaded		
CASING JOINTS: Solved Clamped Welded Threaded Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in., Weight lbs./ft., Wall thickness or gauge No.		
Casing height above land surface		
1 YPE OF SCREEN OR PERFORATION MATERIAL:		
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)		
SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)		
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.		
From		
From		
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other		
Grout Intervals: From		
What is the nearest source of possible cor Septic tank Lateral	ntamination: lines	pens
Sewer lines		
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well		
Direction from well		from well
FROM TO LITHOLO		TO LITHO. LOG (cont.) or PLUGGING INTERVALS
Of 2 Sandy Se	T8	41 Ked Shali
To 15 Gravel	9	
	w/ Sand Streaks	
22 25 Sand		
25 28 Grand Clau		
28 30 Sand Clay		
30 37 tan Clay		
	and	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged		
under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.		
under my jurisdiction and was completed on (mo/day/year)		
under the business name of by (signature) by (signature) by (signature)		
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.		
Telephone 785-296-5522. Send one copy to W.	ATER WELL OWNER and retain one for y	your records. Include fee of \$5.00 for each constructed well. Visit us a
http://www.kdheks.gov/waterwell/index.html.		
KSA 82a-1212		