

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Haskell	SW 1/4 SE 1/4 SW 1/4	5	T 28 S	R 31 EW

Distance and direction from nearest town or city street address of well if located within city?

From east side of Sublette - 6 1/4 miles northeast on Hwy. 56, 8 miles north, 3,745 Ft. W.-50 Ft. N.

2 WATER WELL OWNER: Russell T. Smith Trust & Lorene A. Smith Trust	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # c/o Russell T. Smith - Trustee	Application Number: 20,276
City, State, ZIP Code 222 W. 6th St., Larned, Kansas 67550	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 620 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 297 ft. below land surface measured on mo/day/yr 4-25-96 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 30 in. to 620 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded X
Blank casing diameter See below to ft., Dia. in. to ft., Dia. in. to ft.			Threaded.
Casing height above land surface 12 in., weight 42.05 - 16" lbs./ft. Wall thickness or gauge No. 250			
TYPE OF SCREEN OR PERFORATION MATERIAL:	52.73 - 20" 7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From See below ft. to ft., From ft. to ft., From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 300 ft., From 360 ft. to 620 ft., From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft., From 300 ft. to 360 ft., From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
Direction from well? west				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				How many feet? 611

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		See attached log			
		16" Plain Casing	0	605	
		20" Plain Casing	430	445	
		20" Plain Casing	460	500	
		20" Plain Casing	540	565	
		20" Plain Casing	605	620	
		20" Agri Screen	370	430	
		20" Agri Screen	445	460	
		20" Agri Screen	500	540	
		20" Agri Screen	565	605	
		16" Torch Cut Perf.	605	620	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-29-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 5-2-96 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller
