WATER WELL RECORD Form WWC-5 KSA 82a-1212

Distance and direction from nearest APPROX. 6 MILES NORTH AND 3 1/2 MILE	ES WEST OF COPELAND	 -
	RANCHES %WITHERS OX 68 Board of Agriculture, Division of Water Resourc	es
LOCATE WELL'S LOCATION WITH	: 4 DEPTH OF COMPLETED WELL 650 ELEVATION: 0 : Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3.	0 f
	WELL'S STATIC WATER LEVEL 280 ft. below land surface measured on mo/day/yr 11/ Pump testdata: Well water was 0 ft. after 0 hours pumping	11/9 0 g
	Estimated Yield 0 gpm: Well water was 0 ft. after 0 hours pumping	0 g
	El Bore Hole Diameter 12.25 in. to 650 ft., and in. to 0 ft.	
	: : WELL WATER TO BE USED AS: 01 DOMESTIC	!
SW SE	: 	·
YPE OF BLANK CASING USED: 02 PVC Blank casing diameter 6 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER	If yes, mo/day/yr sample was submitted Water well disinfecte CASING JOINTS: GLUED 1. to 650 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 5 lbs/ft. Wall thickness or gauge No390 RIAL: 07 PVC	ed? \
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 6 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER! SCREEN OR PERFORATION OPENINGS ARE:	If yes, mo/day/yr sample was submitted Water well disinfecte CASING JOINTS: GLUED 1. to 650 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 5 lbs/ft. Wall thickness or gauge No390 RIAL: 07 PVC	ed? Y
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 6 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER! SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to	CASING JOINTS: GLUED 1. to 650 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 5 lbs/ft. Wall thickness or gauge No390 RIAL: 07 PVC 03 MILL SLOT From 410 ft. to 470 ft., From 0 ft. to 0 ft. From 610 ft. to 650 ft., From 0 ft. to 0 ft. From 25 ft. to 650 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. How many feet?	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 6 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERI SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possil Direction from well?	CASING JOINTS: GLUED CASING JOINTS: GLUED The content of the con	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 6 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERI SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possil	If yes, mo/day/yr sample was submitted CASING JOINTS: GLUED 1. to 650 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 5 lbs/ft. Wall thickness or gauge No390 INAL: 07 PVC 03 MILL SLOT From 410 ft. to 470 ft., From 0 ft. to 0 ft. From 610 ft. to 650 ft., From 0 ft. to 0 ft. From 25 ft. to 650 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. How many feet? LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 6 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERI SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possil Direction from well? FROM : TO : I O : 47 : 01 CLAY 47 : 115 : 04 SANDY CLAY 01 115 : 187 : 05 SAND 11 GRAVE	CASING JOINTS: GLUED 1. to 650 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 5 lbs/ft. Wall thickness or gauge No390 RIAL: 07 PVC 03 MILL SLOT From 410 ft. to 470 ft., From 0 ft. to 0 ft. From 610 ft. to 650 ft., From 0 ft. to 0 ft. From 25 ft. to 650 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 17 FINE SAND	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 6 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERIAL SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possil Direction from well? FROM : TO : I	If yes, mo/day/yr sample was submitted	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 6 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERI SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possil Direction from well? FROM : TO : I 0 : 47 : 01 CLAY 47 : 115 : 04 SANDY CLAY 0: 115 : 187 : 05 SAND 11 GRAVI 187 : 200 : 01 CLAY 09 COAR: 200 : 260 : 07 FINE SAND 09	CASING JOINTS: GLUED 1. to 650 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 5 lbs/ft. Wall thickness or gauge No390 NIAL: 07 PVC 03 WILL SLOT From 410 ft. to 470 ft., From 0 ft. to 0 ft. From 610 ft. to 650 ft., From 0 ft. to 0 ft. From 25 ft. to 650 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 6 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER! SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possil Direction from well? FROM : TO : I 0 : 47 : 01 CLAY 47 : 115 : 04 SANDY CLAY 07 115 : 187 : 05 SAND 11 GRAVI 187 : 200 : 01 CLAY 09 COARS 200 : 260 : 07 FINE SAND 09 260 : 277 : 01 CLAY 07 FINE	CASING JOINTS: GLUED 1. to 650 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 5 lbs/ft. Wall thickness or gauge No390 NIAL: 07 PVC 03 WILL SLOT From 410 ft. to 470 ft., From 0 ft. to 0 ft. From 610 ft. to 650 ft., From 0 ft. to 0 ft. From 25 ft. to 650 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 6 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERI SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possil Direction from well? FROM TO 0	CASING JOINTS: GLUED CASING JOINTS: GLUED 1. to 650 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 5 lbs/ft. Wall thickness or gauge No390 RIAL: 07 PVC 03 WILL SLOT From 410 ft. to 470 ft., From 0 ft. to 0 ft. From 610 ft. to 650 ft., From 0 ft. to 0 ft. From 25 ft. to 650 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 6 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERI SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possil Direction from well? FROM : TO : I O : 47 : 01 CLAY 47 : 115 : 04 SANDY CLAY 07 115 : 187 : 05 SAND 11 GRAVI 187 : 200 : 01 CLAY 09 COARS 200 : 260 : 07 FINE SAND 09 260 : 277 : 01 CLAY 07 FINE 277 : 309 : 07 FINE SAND 09 309 : 377 : 01 CLAY	If yes, mo/day/yr sample was submitted	

ı	C	a	n t	i	n	11 /	he	١

WATER WELL RECORD Form WWC-5 KSA 82a-1212

INCATION OF WATER WELL: | Fraction | Section Number | Township Number | Range Number | COUNTY: 041 HASKELL | NE 1/4 NE 1/4 SW 1/4 | 10 | T 28 S | R 31 W WESTERN RANCHES %WITHERS RR#, St. Address, Box # : RT. 1, BOX 68 Board of Agriculture, Division of Water Resources City, State, ZIP code : COPELAND, KS 67837-Application Number: FROM ! TO : LITHOLOGIC LOG 395 | 422 : 07 FINE SAND 09 COARSE SAND 14 MED GRAVEL 422 | 425 | 01 CLAY 425 : 470 : 07 FINE SAND 09 COARSE SAND 14 MED GRAVEL 470 | 472 : 20 LIMESTONE 472 | 591 | 01 CLAY 20 LIMESTONE 07 FINE SAND 596 ! 07 FINE SAND 09 COARSE SAND 14 MED GRAVEL 591 | 596 | 600 | 01 CLAY 20 LIMESTONE 600 | 653 | 07 FINE SAND 09 COARSE SAND 14 MED GRAVEL 653 | 658 | 01 CLAY 658 | 660 |

17 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was : completed on (mo/day/year) 11/11/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 11/18/93

under the business name of HENKLE DRILLING & SUPPLY

by (signature) Brung Reichmant