WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Haskell | Fraction: ¼ ¼ SW ¼ | Section Number: 17 | Township Number: T 28 S | Range Number: R 33 E(W)

Distance and direction from nearest town or city? Sublette - 1½ West Street address of well if located within city? 9 North - 4 5/8 West - ½ North

2 WATER WELL OWNER: Glenn Converse (Mrs.)
RR#, St. Address, Box # : 1024 W. 4
City, State, ZIP Code : Larned, KS 67550
Board of Agriculture, Division of Water Resources Application Number:

3 DEPTH OF COMPLETED WELL 450 ft. Bore Hole Diameter 26 in. to 450 ft., and in. to ft.

Well Water to be used as: 1 Domestic 3 Feedlot 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Observation well 11 Injection well 12 Other (Specify below)
(2) Irrigation 4 Industrial

Well's static water level 335 Approx. below land surface measured on January month 16 day 1980 year
Pump Test Data: Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED: (1) Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)
Casing Joints: Glued Clamped Welded X Threaded
Blank casing dia 16 in. to 450 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface 12 in., weight 36.4 lbs./ft. Wall thickness or gauge No .219

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass (4) Galvanized steel 3 Stainless steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

Screen or Perforation Openings Are: 1 Continuous slot (3) Mill slot 2 Louvered shutter 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

Screen-Perforation Dia 16 in. to 450 ft., Dia in. to ft., Dia in. to ft.
Screen-Perforated Intervals: ~~From~~ Screen 350-375 ft. xx Perf 375-385 ft., ~~From~~ Screen 385-415 ft. xx Perf 415-425 ft.
~~From~~ Screen 425-445 ft. xx Perf 445-450 ft., From ft. to ft.
Gravel Pack Intervals: From 10 ft. to 450 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement (2) Cement grout 3 Bentonite 4 Other
Grouted Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Lateral lines 4 Cess pool 5 Seepage pit 6 Pit privy 7 Sewage lagoon 8 Feed yard 9 Livestock pens 10 Fuel storage 11 Fertilizer storage 12 Insecticide storage 13 Watertight sewer lines 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
Center of ½ Section N/A
Direction from well How many feet ? Water Well Disinfected? Yes No X
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, date sample was submitted month day year: Pump Installed? Yes X No
If Yes: Pump Manufacturer's name Used Customers Pump Model No. HP Volts
Depth of Pump Intake 460 ft. Pumps Capacity rated at gal./min.
Type of pump: 1 Submersible (2) Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on July month 28 day 1980 year and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208
This Water Well Record was completed on October month 23 day 1980 year under the business name of Minter Wilson Drilling Co., Inc. by (signature)

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



ELEVATION:

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
		Test log attached			

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, *please press firmly* and *PRINT* clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 28 R 33 W SEC 17 ¼ C of SW¼

The Professional MINTER-WILSON DRILLING CO.

[illegible] CITY, KANSAS

January 1[illegible], 1980

Scott [illegible]
Haskell County

Location: SW 17-28-33 - Test Hole next to rail water pit
Static Water Level [illegible]335
Test [illegible]

0	1	Top Soil
1	55	Brown Clay
55	93	Med. to Coarse Gravel (Loose)
93	155	Fine to Med. Sand & Gravel Streaks of Coarse Gravel (Loose)
155	179	Brown Clay 30% Gravel
179	214	Fine to Med. Sand & Gravel 10% Clay (Loose)
214	220	Brown Clay
220	228	Fine to Med. Sand & Gravel 10% Clay (Loose)
228	245	Fine to Med. Sand & Fine Gravel 20% Clay (Loose)
245	269	Fine to Med. Sand & Gravel 15% Clay (Loose)
269	290	Brown Clay
290	303	Blue Clay
303	374	Fine to Med. Sand & Gravel (Loose)
374	385	Brown Clay
385	418	Fine to Med. Sand & Gravel 10% Clay (Loose)
418	425	Brown Sandy Clay
425	448	Fine to Med. Sand & Gravel (Loose)
448	458	Brown Clay (Tight)
458	485	Brown & Gray Clay with White Rock (Hard)
485	504	Gray & Yellow Clay with Brown & White Rock (Hard)
504	510	Shale (Hard)

T.D. 450