


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: HASKELL		SE 1/4 NE 1/4 NE 1/4	20	T 28 S	R 33 E/W
Distance and direction from nearest town or city street address of well if located within city? 6 North, 4 West, 2 1/2 North of Sublette, Kansas					
2 WATER WELL OWNER:		Marion Daugherty			
RR#, St. Address, Box # :		Box 86			
City, State, ZIP Code :		Sublette, Kansas 67877			
Board of Agriculture, Division of Water Resources		Application Number: ---			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 440 ft. ELEVATION: Slope			
		Depth(s) Groundwater Encountered 1. Not available ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 345 ft. below land surface measured on mo/day/yr August 15, 1986			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 20 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 9 7/8 in. to 440 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No. XX If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes XX No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued XX Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
XX PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 5 in. to 400 ft., Dia. in. to ft., Dia. in. to ft.		7 Fiberglass			
Casing height above land surface 15 in., weight 2.8 lbs./ft. Wall thickness or gauge No. 265		Threaded			
TYPE OF SCREEN OR PERFORATION MATERIAL:		XX PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped XX Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 400 ft. to 440 ft., From ft. to ft.		From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 14 ft. to 440 ft., From ft. to ft.		From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: XX Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 4 ft. to 14 ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
XX Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		Direction from well? South How many feet? 100			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	49	6 Clay			
47	120	07 Fine Sand			
120	174	04 Clay and Fine Sand			
174	291	07 Fine Sand			
291	314	01 Clay			
314	394	04 Clay and Fine Sand			
394	438	17 Med. to Lar. Sand and Gravel			
438	440	Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) ... August 18, 1986 ... and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/yr) ... August 28, 1986 ... under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

9300000000-90