		WATER	R WELL RECORD I	orm WWC-5	KSA 82a	-1212			
1 LOCATION OF W	ATER WELL:	Fraction		Sec	ction Number	Township N	lumber	Range Nu	ımber
County: Haske		SE 1/4	SE ¼ SE		36	T 28	S	R 33	E/ (()
		•	dress of well if located	•					
			west of Subl						
2 WATER WELL O	WNER: 01d San	ta Fe Feed	lers We	st well	of the b	attery of (2) well	ន	
RR#, St. Address, B	ox # :						-	Division of Water	r Resource:
City, State, ZIP Code	: Sublett	e, KS 678	377			Applicatio	n Number:	33,980	
LOCATE WELL'S AN "X" IN SECTION	LOCATION WITH 4 ON BOX:	DEPTH OF CO	OMPLETED WELL vater Encountered 1.	608'	. ft. ELEVA	TION:			
- C			WATER LEVEL . 32						
i i	1 1 1"		test data: Well water						
NW	NE) gpm: Well water				•		
! ! !			ter17½in. to .						
# w 1				5 Public wate		8 Air conditioning		Injection well	
_							-	•	(میرمام
sw	SE	1 Domestic				9 Dewatering			
		2 Irrigation				10 Observation w			
<u> </u>		as a cnemical/b	acteriological sample su	Library to D		ter Well Disinfect			DIE Was suc
TYPE OF BLANK	CASING USED:		5 Wrought iron	8 Concr	ete tile	CASING JO	INTS: Glued	I Clamp	ed
1 Steel	3 RMP (SR)		6 Asbestos-Cement	9 Other	(specify below	v)		ed	
2 PVC	4 ABS		7 Fiberglass					ded	
Blank casing diameter	er 8.'' in.	. to 608.'.	ft., Dia	in. to		ft., Dia		in. to	ft.
Casing height above	land surface12	. 	in., weight	19.66	Ibs./	ft. Wall thickness	or gauge N	219" &	. 203"
TYPE OF SCREEN	OR PERFORATION I	MATERIAL:		7 PV	C	10 As	pestos-ceme	nt	
1 Steel	3 Stainless s	teel	5 Fiberglass	8 RN	IP (SR)	11 Ot	ner (specify)		
2 Brass	4 Galvanized		6 Concrete tile	9 AB	` '		ne used (op		
	PRATION OPENINGS			d wrapped	_	8 Saw cut	(-,-	11 None (oper	n hole)
1 Continuous s				rapped		9 Drilled holes		(,
2 Louvered shu	_		7 Torch	• •		10 Other (specif	v)		
SCREEN-PERFORA		From 386-4	4.66 ft. to . 4		ft Fro				
OONEEN EN OFF	TED INTERVALO.		ft. to						
GRAVEL P	ACK INTERVALS:		ft. to						
GIBATEL					•		ft. t		ft
6 GROUT MATERIA	I Neat cen	nent 3	Cement grout	3 Bento	nite 4	Other			
	om 0 ft.	10'	ft. to Cement grout ft., From	ft	to	•			
	source of possible co	ntamination:			10 Lives	tock pens		bandoned water	
1 Septic tank	4 Lateral		7 Pit privy		11 Fuel	•		il well/Gas well	*****
•	5 Cess po		8 Sewage lago			_		ther (specify be	loud)
2 Sewer lines			• •	OII		zer storage ticide storage	10 0	tries (specify be	OW)
	wer lines 6 Seepag	e pit	9 Feedyard			•			
Direction from well? FROM TO	North	LITHOLOGIC L	06	FROM	TO How man	ny feet? 200 d	LITHOLOG	IC LOG	
PROM 10	Coo ott	ached log	.00	THOW	 '		LITTIOLOG	io Lou	
	see att	actied tog		+	 				
				-	-				
				+	 				
				+	 				
				1					
				-					
7 CONTRACTORIO	OR LANDOWNERS	CERTIFICATION	ON: This water well wa	e (1) const-	icted (2) ross	netructed or (2)	olugged use	ler my juriediatia	n and wa
			ON: I'nis water well wa						
completed on (mo/da	y/year) 2-9-87						est of my kn 2-18		nei. Nansas
			This Water We			<i>L</i>	····///	D	J
under the business f	name of Henkle D	rilling &	Supply Co., I	IIC .	by (signa		appropriate Con	od top three copies	to Kansas
			ironmental Geology, Regula						
	/NER and retain one for				5 5 5 5 6 6 7 7 7 7 7 7 7 7 7 7 7 7 7 7		. 223, . 310pm		

DRILLERS TEST LOG

CUSTOMERS NAME	Old Santa Fe Feeders	DATE 2-5-87
STREET ADDRESS		TEST #1-WestE. LOG Yes
CITY & STATE	Sublette, KS 67877	TEST #1-WestE. LOG Yes DRILLER Livingston
COUNTY Haskell	QUARTER SE SECTION	36 TOWNSHIP 28 RANGE 33

LOCATION 610 ft. West and 300 ft. North of the center of 83 ft.

	WE	ST WE	LL OF	THE BATTERY OF TWO WELLS WELL LOCATION
%	FOOTAGE			Static Water Level
~	From Pay To			DESCRIPTION OF STRATA Proposed Well Depth
0 2				Top Soil
	2		50	Brown sandy clay, caliche and few fine sand streaks
	50		58	Sand, fine to medium
	58		80	Brown sandy clay and limerock
	80		190	Sand, fine to medium, small to large gravel
	190		200	Brown sandy clay and sand streaks
	200		229	Brown clay
	229		330	Blue clay - sticky
	330		352	Blue clay and blue-sand, fine, small
50	352	18	370	Sand, fine to medium, few coarse
60	370	11	381	Sand, fine to medium, coarse, small gravel
	381		387	Sandy clay, limerock and fine sand
65	387	3 5	422	Sand, fine to medium, coarse, few small gravel, cemented
		<u> </u>		from 408' - 422'
40	422	24	446	Brown sandy clay, limerock ledges and sand fine to
				medium, few coarse.
	446		481	Brown sandy clay, limerock and few fine sand streaks
35	481	19	500	Sand, fine, small and few clay streaks
	500		540	Brown clay, limerock and few fine sand streaks
	540		553	Sand, fine and clay
	553		558	Brown clay and limerock and few fine sand streaks
70	558	22	580	Sand, fine to medium, coarse, small brown gravel and
	<u> </u>	ļ	 	brown raock and few clay streaks
	580	1	590	Brown clay and few sand streaks
70	590	15	605	Sand, fine to medium, coarse, small brown gravel and
		-	 	brown rock - drills rough
	605	╀	620	Brown clay, soapstone, and limestone
-	╂───	 	 	TOTAL DEPTH 608'
	1	1-	1	
	 	1-	1	Set Up SE Pit on the South
	 	1	1	I I I Ou the bouth
	1	1	-	
	 -	1	1	
	 	1-	1	
	1	1		
			1	
	1	1		
		1		

GARDEN CITY, KS HENKLE DRILLING & SUPPLY CO., INC. SUBLETTE, KS Phone 276-3278 IRRIGATION HEADQUARTERS Phone 675-4311