

1 LOCATION OF WATER WELL:		Fraction	Section		Township Number		Range Number	
County: <b>Haskell</b>		<b>NW</b> $\frac{1}{4}$ <b>SW</b> $\frac{1}{4}$ <b>SE</b> $\frac{1}{4}$	<b>4</b>		<b>T 28 S</b>		<b>R 34 E/W</b>	

Distance and direction from nearest town or city street address of well if located within city?  
**North of Sublette to Hwy 160 10 West 5 North ½ East ¼ North**

2	WATER WELL OWNER:	Cooper F#4	OXY USA INC	Board of Agriculture, Division of Water Resources
	RR#, St. Address, Box # :		BOX 26100	
	City, State, ZIP Code :		OKLAHOMA CITY OK 73126	Application Number: 910061

1 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

N

NW	NE
SW	SE

S

W                      E

2 DEPTH OF COMPLETED WELL. 420 ft. ELEVATION: .....

Depth(s) Groundwater Encountered 1. 100 ft. 2. .... ft. 3. .... ft.

WELL'S STATIC WATER LEVEL 320 ft. below land surface measured on mo/day/yr 4-2-91

Pump test data: Well water was 345 ft. after 2 hours pumping 40 gpm

Est. Yield 50 gpm: Well water was .... ft. after .... hours pumping .... gpm

Bore Hole Diameter. 9 in. to 420 ft., and, .... in. to .... ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	<u>6 Oil field water supply</u>
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes.....No. X.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input type="checkbox"/>
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
<u>2 PVC</u>	4 ABS	7 Fiberglass		Threaded

Blank casing diameter 5 in. to 320 ft., Dia.      in. to      ft., Dia.      in. to      ft.

Casing height above land surface 14 in., weight 200 lbs./ft. Wall thickness or gauge No. 0.265

TYPE OF SCREEN OR PERFORATION MATERIAL:		<u>7 PVC</u>	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
			11 Other (specify) <u>    </u>
			12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	<u>8 Saw cut</u>	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify) <u>    </u>	

SCREEN-PERFORATED INTERVALS: From 320 ft. to 420 ft., From      ft. to      ft., From      ft. to      ft.

GRAVEL PACK INTERVALS: From 310 ft. to 420 ft., From      ft. to      ft., From      ft. to      ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? Southwest How many feet? 250

[illegible]

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-2-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 4-5-91 under the business name of T & W Water Well Service, Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.