## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction		Section number		Township number	Range number		
1. Location of well:	Haskell	NW 1/4 NW 1/4 SW	1/4	1	3	T 28 S	R 34	E/W	
2. Distance and direction from nearest town or city: 9 mi. N, 7 mi. 3. Owner						Nellie Freeman		_	
W, of Sublette, Kansas.  Street address of well location if in city:						201½ Harrington			
City, stat					ode:	Augusta, Kansa:  6. Bore hole dia. 28 in.		/29/16	
4. Locate with "X" in section below:  Sketch map:						Well depth 4.63 ft.	Completion data.	1	
1						7 Cable tool Rotary	Driven Dug		
NW NE 350' E of NW corner of SW4,						Hollow rod Jetted			
Sec. 13, T28S, R34W, Haskell County, Kansas.						8. Use: Domestic Pu	ublic supply Indu ir conditioning Stor	, I	
[7   1   1   1   1   1   1   1   1   1						Lawn Oil field water Other			
						9. Casing: Material Stl Height: Above or below Threaded Welded Surface in.		olow .	
						RMP PVC	!Weight <u>37</u>	_ibs./ft.	
1→ 1 Mile → 1						Dia. 16 in. to 283 ft. dep	th Wall Thickness: inc	hes or	
5. Type and color of material				From	То	Diain. toft. depth gage No219  10. Screen: Manufacturer's nameFoster. Cook			
						Doerr	louver		
Top soil				0	4	Type milslot, w Slot/gauze 1/8"	₩ Dia _ Length180		
Tan sandy clay				2	61	283 <sub>between</sub> <u>283</u>	ft. and 463	ft.	
Fine to coarse sand med. to coarse gravel with				h		Gravel pack <b>7 C.S.</b> Size ra		4mm **	
tan clay streaks				61	155	11. Static water level: mo./day/yr.  299 ft. below land surface Date 7/10/76			
Fine to coarse sand med, to coarse gravel				155	200	12. Pumping level below land	surfaces:		
				200	210	12. Pumping level below land surfaces:   318    ft. after			
Tan sandy clay				200	210	Estimated maximum yield 1500 g.p.m.			
Blue clay				210	292	13. Water sample submitted: mo./day/yr.			
Fine to coarse sand med. to coarse gravel				292	320	14. Well head completion:			
Fine to go	erse sand med to	andree grave	1	h		Pitless adapter	X Inches above g	grade	
Fine to coarse sand med. to coarse gravel wit						15. Well grouted? Yes With: Neat cement X	Bentonite C	Concrete	
tan clay streaks				320	378	Depins roll			
Tan & blue clay (sandy) with sand streaks				378	394	16. Nearest source of possibl		k	
Fine to coarse sand med, to coarse gravel wit				h		Well disinfected upon comple	'	No	
					460	17. Pump:  Manufacturer's name	Not installed	×	
tan and blue clay streaks				394	463	Model number 12 DC	HP <u>105</u> vol	<u>+</u>	
Tan & blue sandy clay with sand streaks				463	500	Length of drop pipe <u>380</u> Type:	_ ft. capacity 125	g.p.m.	
						Submersible	X Turbine		
(Use a second sheet if needed)						Jet Centrifugal	Recipro	cating	
18. Elevation:	19. Remarks:	should it liesued/			L	20. Water well contractor's		°	
						This well was drilled under my jurisdiction and this report			
Topography:						is true to the best of my know  Lavne-Western		102	
Hill						Business name	Lice	ense No.	
Slope X_Upland						AddressGarden C	Kansa	}	
Valley						Signed Authorized rep	presentative /8 /2	×76	
Cammand the subite bl	tue and nink conies to the Departmen						Form WW	C-5	