WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	Loui	F				T 12 1	I 9		
1. Location of well:	County	Fraction		Section number		Township number	Range number		
		SE 1/4 SW 1/4 SW					R 34	E/W_	
					er of well: Arlie Stonestreet street: % Stonestreet Farms				
Street Holderstat well because it in the body					rate, zip code:Satanta, Kansas 67870				
4. Locate with "X" in section below: Sketch map:					- 54	6. Bore hole dia. 28 in	. Completion date Z	<u>-29-</u> 77	
N						Well depth 422 ft.			
300' N and 990' E of the SW							rod Botary Driven Dug rod Jetted Bored X Reverse rotary		
corner of the SW4, Sec. 14,						8. Use: Domestic Public supply Industry			
T28S, R34W, Haskell County,						🗴 Irrigation Air conditioning Stock			
i						Lawn Oil field water Other			
						9. Casing: Material Stl Height: Above or below Threaded Welded X Surface 12 in.			
S						RMP PVCWeight37lbs./ft.			
ı——1 Mile ——⊶ı						Dia. 16 in. to 310ft, depth Wall Thickness: inches or Dia in. to ft. depth gage No 219			
5. Type and color of material					То	10. Screen: Manufacturer's name Foster, Cook			
m : 1				0	10	Doerr Louv			
Top soil				10		Slot/gauze 1/8, 1/64 Length 112			
Tan sandy clay				10	62	Set between <u>310</u>	_ft. and422_	ft.	
Fine to coarse sand				62	170	ft. andft. Gravel pack? X Size range of material 3.3 mm			
				170	180	11. Static water level: mo./day/yr.			
Tan clay				1		292 ft. below land surface Date 5-20-77			
Fine to medium sand				180	236	12. Pumping level below land 334ft. after		3 g.p.m.	
Tan clay				236	268	350ft. after 1 hrs. pumping 1500 g.p.m.			
				268	294	Estimated maximum yield			
Fine sand				1		Yes _XNo Date			
Tan clay				294	315	14. Well head completion:			
Fine sand dirty				315	347	Pitless adapter 15. Well grouted?	X Inches above	grade	
				247	202	With:Neat_cement _XBentoniteConcrete			
Fine to medium sand					382	Depth: FromO ft. to1O_ ft.			
Fine sand clay streaks				382	422	16. Nearest source of possible contamination: unk ft Direction Type			
Tan clay red bed streaks				422	440	Well disinfected upon comple		No	
						17. Pump: Manufacturer's name Lay	Not installed	. 12	
				1		Model number 12TL	_ HP <u>200</u> vo	olts	
						Length of drop pipe 400 Type:	ft. capacity 14 (∆ Ø. _{p.m} .	
						Submersible	<u>X</u> Turbin	ne	
(Use a second sheet if needed)						Jet	Recipr	rocating S	
18. Elevation:	(Use a second s	incer it needed/		1	1	Centrifugal 20. Water well contractor's			
Eletailoli;	North and					This well was drilled under m	ny jurisdiction and thi	is report	
Topography:						is true to the best of my know	•	102	
— Hill						Layne-Westerr	Lic	cense No.	
Slope						Address Garden	City, Kans	<u>as</u>	
Upland Upland Valley						Signe Authorized rep	presentative S	477	
	ue and pink copies to the Department	of Health and Environment					Form W	WC-5	

MI-1023