

1 LOCATION OF WATER WELL: County: <u>Haskell</u>		Fraction <u>SE ¼ SE ¼ SW ¼</u>	Section Number <u>24</u>	Township Number <u>T 28 S</u>	Range Number <u>R 34 E/W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>From Sublette - 1 Mile SW on Hwy. 56, 8 Miles North, 6 Miles West, 120 Ft. North & 3330 Ft. West</u>					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		<u>Tice Cattle Company</u> <u>HCR 1 - Box 20</u> <u>Sublette, Kansas 67877</u>			
		Board of Agriculture, Division of Water Resources Application Number: <u>5135-ST</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL. <u>535</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1.....ft. 2.....ft. 3.....ft.			
		WELL'S STATIC WATER LEVEL <u>357</u> ft. below land surface measured on mo/day/yr <u>5-14-93</u>			
		Pump test data: Well water wasft. after hours pumping gpm			
		Est. Yield gpm: Well water wasft. after hours pumping gpm			
		Bore Hole Diameter <u>30</u> in. to <u>535</u> ft., andin. toft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u>; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
① Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded			
Blank casing diameter16.....in. to390.....ft., Dia.....in. toft., Dia.....in. toft.					
Casing height above land surface.....12.....in., weight <u>42.05</u> lbs./ft. Wall thickness or gauge No. <u>250</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
① Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot ③ Mill slot ⑥ Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From.....390.....ft. to535.....ft., From.....ft. to.....ft.					
GRAVEL PACK INTERVALS: From.....26.....ft. to535.....ft., From.....ft. to.....ft.					
From.....ft. to.....ft., From.....ft. to.....ft.					
6 GROUT MATERIAL: 1 Neat cement ② Cement grout 3 Bentonite 4 Other					
Grout Intervals: From.....6.....ft. to26.....ft., From.....ft. to.....ft., From.....ft. to.....ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		<u>NONE</u>			
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		See attached log			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, ② reconstructed, or ③ plugged under my jurisdiction and was completed on (mo/day/year) <u>6-30-93</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>208</u> . This Water Well Record was completed on (mo/day/yr) <u>7-26-93</u> under the business name of <u>Minter-Wilson Drilling Co., Inc.</u> by (signature) <u>Nora Keller</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					