	Frank			ELL RECORD	Form WW	C-5 KSA 8	32a-1212	<u> </u>			
_	TION OF WA	TER WELL:	Fraction	-		Section Numb	er	Township Nur	nber	Range Number	
County:	Hask	ell	SE 1/4 N	E 1/4	NE 14	26		T 28	S	R 34 W E(W)	
Distance	and direction	from nearest town	or city street addres	s of well if loca	ited within ci	<sup>y?</sup> Satan	ta. 1	Kansas ·	- 1/4	mile West -	
. 10	miles	North - We	est into lo	cation.					•		
	ER WELL OV		lo Wright J				÷1 0	il Comm	/ TIm:	± 10	
_	. Address, Bo					MOD	11 0	Board of Ag	· / Un.	it 19 Division of Water Resource:	
	te, ZIP Code				Application	Number:	T 88-70				
			nta, Kansa		440'	4 ELE	VATION		Turribor.		
H AN "X	" IN SECTIO										
_		N   L									
Ī											
11	NW	NE								mping gpm	
	l "i"		st. Yield . LOO	gpm: Well wa	ater was	ft	. after .		hours pur	mping gpm	
e w	1	┖┸┸┛╏	Bore Hole Diameter.	1.1."in. 1	to <del>4</del> .4	:0.•	t., and		in.	toft.	
M Mile	!	v	VELL WATER TO BE	E USED AS:	5 Public v	water supply	8 Air	conditioning	11	Injection well	
î .	SW	!	1 Domestic	3 Feedlot	6 Oil field	water supply	9 De	watering	12	Other (Specify below)	
	sw	3E	2 Irrigation	4 Industrial	7 Lawn a	nd garden only	y 10 Ot	servation well			
	li	l i l lv	Vas a chemical/bacte	riological sample						mo/day/yr sample was sub	
I			nitted	J				ell Disinfected	_	X No	
5 TYPE	OF BLANK	CASING USED:		Vrought iron	8 00	ncrete tile				I Clamped	
	Steel	3 RMP (SR)		Asbestos-Cemer		her (specify be		CASING JOIN		ed	
	PVC	4 ABS					•				
	aina diamata			iberglass				D:	inrea	ided	
Blank ca	sing diameter	7Q.&QAQII	1. 10	. π., Dia		. to	π	., Dia		in. to ft.	
				weight			bs./ft. Wa			<sub>0.</sub> • 2.80	
		R PERFORATION			$\overline{}$				stos-ceme		
1 5	Steel	3 Stainless	steel 5 F	iberglass	8	RMP (SR)		11 Othe	r (specify)		
2 E	Brass	4 Galvanize	d steel 6 C	Concrete tile	9	ABS		12 None	used (op	en hole)	
SCREEN	OR PERFO	RATION OPENING	S ARE:	5 Ga	uzed wrappe	đ	<b>.</b>	Saw cut		11 None (open hole)	
1 (	Continuous sl	ot 3 Mill	slot	6 Wir	e wrapped		9 [	Orilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From											
										o	
	GRAVEL PA	ACK INTERVALS:	From 25!	ft. to	320.		From	330	ft. t	o440!ft.	
			From							o ft.	
6 GRO	JT MATERIA	L: 1 Neat ce		ement grout		entonite					
										ft. to	
		ource of possible c		,	<del></del>		vestock p			bandoned water well	
l .		4 Lateral		7 Pit privy							
2 Sewer lines 5 Cess po							11 Fuel storage 15 Oil well/Gas well				
3 Watertight sewer lines 6 Seepage				5 5			12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage				
I .	-	•	• .	9 Feedyard				•			
FROM	from well?	Northw					many fee	et? 200'	ITUOI OO	10 1 00	
		G	LITHOLOGIC LOG		FRO				ITHOLOG	IC LOG	
0	5	T	Bickfill		98 cu.			ckfill			
5	25		te Grout	3.				ntonite			
25	320		ated gravel					lorinat		4	
320	330	Bentoni	te Grout	1.	96 cu.	, feet o	of Be	ntonite	grou	t	
330	440	Chlorin	ated gravel	21.	59 cu.	feetoi	Chl	orinate	d gra	vel	
										•	
l	<del>-</del>					-					
<b>-</b>							+			<del></del>	
ļ. —	L					1					
7 CON	TRACTOR'S	OR LANDOWNER	S CERTIFICATION:	This water well	was (1) cor	structed, (2) r	econstru	cted, ot (3) pl	ugged und	ler my jurisdiction and was	
complete	d on (mo/day	<sub>//year)</sub> 03/	77 /00							owledge and belief. Kansas	
Water Well Contractor's License No											
			e WaterWel					126			
										nd top three copies to Kansas	
										/NER and retain one for your	

records.