WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| . Location of well: | County Haskell | Fraction SW SE SW | | Section number | | Township number | Range number | |
|--|-------------------|----------------------|--|---|----|--|----------------------------------|------------------|
| Distance and dis- | | | | | | Philo Wright |] R | E, (2) |
| Sublette Jct., 8 west, $1\frac{1}{2}$ north R.R. of | | | | vner of well: or street: state, zip code: | | Satanta, Ks. 67870 | | |
| 4. Locate with "X" in section below: N | | | | | | 6. Bore hole dia. <u>26</u> in Well depth <u>455</u> ft. | . Completion date 5. | -31- 7 |
| NW | NE | | | | | 7 Cable tool Rotary Hollow rod Jetted | | se rotary |
| W | | | | | | 8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other | | |
| sw x | SE | | | | | 9. Casing: Material STEE Threaded Welded X | 1 Height: Above er | nten/= |
| \$ | | | | | | RMP PVC Dia. 16 in. to 456ft. dep | Weight <u>36 87</u> | lbs./ft. |
| i. Type and color of | | | | From | То | Dia in. to ft. dep | th gage No. | 250_ |
| 7. Type and color of material | | | | | | 10. Screen: Manufacturer's | | |
| | | | | | | Type galv. | | |
| | | | | | | Slot/mass 420 | Length 20 ft | •— |
| | | | | | | Perf:200-420 ft. | and 440-455 | ft. |
| | | | | | | Gravel pack? <u>Yes</u> Size ra | nge of material 211 | down |
| _ | | | | | | 11. Static water level:260 ft. below land sui | face Date _5-17 | /day/yr. - 77 |
| | | | | | | 12. Pumping level below land 275 ft. after 2 | | |
| | | | | | | 280 ft. after 4 | hrs. pumping $\frac{1100}{1600}$ | g.p.m. |
| | | | | | | Estimated maximum yield | 1600 | g.p.m. |
| | | | | | | 13. Water sample submitted: | | /day/yr. |
| | | | | | | Yes X No 14. Well head completion: | Date | |
| | | | | | | Pitless adapter | 12 Inches above s | grade |
| | | | | | | 15. Well grouted? <u>Yes</u> With: Neat cement | Rentonita X C | onerete |
| | | | | | | Depth: From ft. to | 7.0 | .oncrete |
| | | | | | | 16. Nearest source of possible ft Direction | e contamination: N/ | A |
| | | | | | | Well disinfected upon comple | | X No |
| | | | | | | 17. Pump: Manufacturer's name GO | Not installed | ווווח |
| | | | | | | Model number 14JHMC | HP_200 Vol | hs |
| | | | | | | Length of drop pipe 400 | ft. capacity 120 | .Q.p.m. |
| | | | | | | Submersible | X Turbine | |
| | (Lise a second | sheet if needed) | | | | Jet Centrifugal | Recipro | cating |
| 18. Elevation: | 19. Remarks: | , | | | | 20. Water well contractor's | certification: | |
| | | 2 | | | 7 | This well was drilled under no is true to the best of my know | , i | report 208 |
| Topography: | | | | | | Minter-Wilson I | | , Inc |
| Hill Slope | | | | | | Business name BOX A Gar | den City, lig | nse No. |
| Upland | | | | | | De Le | B. 19- | 30-77 |
| Valley | | | | ٠. | | Authorized re | presentative | |

MINTER-WILSON DRILLING CO. Complete Installation

#UBB 276-3269 . P.O. Box A . GARDEN CITY, KANSAS 67846

PHILO WRIGHT HASRELL COUNTY 3/28/77

Location:

SW 26-28-34 8 miles west of Santa Fe Teeders

13 north & east

Static Water Level- 280' Test #1

| 0 | 4 | Top soil |
|-----|-----|---------------------------------------|
| 4 | 42 | Brown clay |
| 42 | 66 | Fine to med. sand and gravel |
| 66 | 81 | Med. to course gravel |
| 81, | 111 | Fine to med. sand and gravel |
| 111 | 126 | Med. to course gravel |
| 126 | 212 | Fine to med. sand and gravel |
| 212 | 223 | Sandy clay |
| 223 | 312 | Fine to med. sand and gravel |
| 312 | 321 | Clay |
| 321 | 364 | Fine to med. sand and gravel |
| 364 | 380 | Fine to med. sand and gravel 15% clay |
| 380 | 396 | Fine to med. sand and gravel |
| 396 | 408 | Brown sandy clay |
| 408 | 455 | Fine to med. sand and gravel |

T.D. 455 Screen 20 220' - Plain 200° - Perf 20' - Screen 15' - Perf