

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Haskell	Fraction SW 1/4 SE 1/4 SE 1/4	Section number 34	Township number T 28 S R 34 E/W	Range number 34
2. Distance and direction from nearest town or city: 0 1/4 miles west of Satanta, Ks. 8 1/2 North, 1 West of Satanta, Ks.		3. Owner of well: George Doerkson		R.R. or street: Satanta, Kansas 67870		
4. Locate with "X" in section below: N W E S 1 Mile 1 Mile		Sketch map: 		6. Bore hole dia 9 7/8 in. Completion date _____ Well depth 480 ft. 3-21-77		
5. Type and color of material		From	To	7. <input type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
Top soil		0	8	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Tan clay		8	43	9. Casing: Material PVC Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight 2.8 lbs./ft. Dia. 5 in. to 480 ft. depth Wall Thickness: inches or Dia. _____ in. to _____ ft. depth gage No. 265		
Fine sand		43	56	10. Screen: Manufacturer's name Jess & Lowell Type PVC Dia. 5" Slot/groove 1/8" Length 100' Set between <input checked="" type="checkbox"/> 280 ft. and <input checked="" type="checkbox"/> 480 ft. 440 ft. and 480 ft. Gravel pack? Yes Size range of material #1 fine		
Med. sand with gravel streaks		56	155	11. Static water level: _____ mo./day/yr. 225 ft. below land surface Date 3/17/77		
Yellow clay		155	176	12. Pumping level below land surfaces: _____ ft. after _____ hrs. pumping _____ g.p.m. _____ ft. after _____ hrs. pumping _____ g.p.m. Estimated maximum yield 40 g.p.m.		
Med. to lar. sand		176	185	13. Water sample submitted: _____ mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date _____		
Yellow clay		185	210	14. Well head completion: XX Pitless adapter Unit _____ Inches above grade		
Med. to lar. sand with yellow clay streaks		210	460	15. Well grouted? Yes With: _____ Neat cement _____ Bentonite XX Concrete Depth: From 4 ft. to 14 ft.		
Sandy clay		460	490	16. Nearest source of possible contamination: ft. 150 Direction North Type sewer Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
(Use a second sheet if needed)				17. Pump: _____ Not installed Manufacturer's name Aermotor Model number SD12 HP 2 Volts 220 Length of drop pipe 315 ft. capacity 10 g.p.m. Type: <input checked="" type="checkbox"/> Submersible _____ Turbine _____ Jet _____ Reciprocating _____ Centrifugal _____ Other		
18. Elevation:	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Friesen Windmill 252 Business name License No. Address Meade, Kansas 67864 Signed [Signature] Date 4-8-77 Authorized representative			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5