WATER WELL REC	OKD	Form W	WC-5	Di	ivision of Wate	r Resources App. N	0. ———	
1 LOCATION OF WATER WELL: County: HASKELL		Fraction  1/4 SE 1/4 SE	1/4 SE !	1	on Number 27	Township No. T 28 S	Range Number R 34 □E ☑W	
Street/Rural Address of Well Location; if unknown, distance &			direction	Globa	Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here					Latitude: (in decimal degrees) Longitude: (in decimal degrees)			
FROM JCT 56 & 83 IN SUBLETTE: 6 W TO HWY 160, 8W, 1 1/4 N TO LOC ON W SIDE					Elevation: (in decimal degrees)			
				Datur	Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: SW WINDMILL RR#, Street Address, Box #: P.O. BOX 909				Colle	Collection Method:  GPS unit (Make/Model:)			
City, State, ZIP Code : MEADE, KS 67864					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
					Est. Accuracy:			
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 520 ft.								
SECTION BOX:	BOX: Depth(s) Groundwater Encountered (1).290 ft. (2)							
N	WELL'S STATIC WATER LEVEL. 290ft. below land surface measured on mo/day/yr. 3-18-09							
Pump test data: Well water was .441								
		/8in. to .520ft., andin. toft.						
	TO BE USED AS:	Public water supply Geothermal Injection well						
SWSE								
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well								
S If yes, mo/day/yr sample was submitted							:	
mile  Water well disinfected? ☑ Yes ☐ No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .5. in. to .460. ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface .24. in., Weight 3.706								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:								
SCREEN OR PERFORATION OPENINGS ARE:  Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS:         From								
GRAVEL PACK INTERVALS: From 280 ft. to 520 ft., From ft. to ft.								
From ft. to ft. From ft. ft ft.								
6 GROUT MATERIAL: ✓ Neat cement ☐ Cement grout ☐ Bentonite ✓ Other HOLE PLUG								
Grout Intervals: From .1								
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel st								
☐ Watertight sewer lines     ☐ Seepage pit     ☐ Feedyard     ☐ Fertilizer storage     ☐ Oil well/gas well       Direction from well     Distance from well								
FROM TO	LITHOLOG		FROM	ТО			GGING INTERVALS	
0 2 TOP SO			345	410	MED. SAN			
	E & TAN CLAY		410	423	FINE SAN			
23 47 SANDY 47 88 SAND	CLAY & SAND		423 445	445 478	MED. SAN	LAY STREAKS		
	E SAND & MEI	D. SAND	445	482	CLAY	U		
	CLAY & SAND STREAKS			517	SAND			
	MED. SAND 517			525	BLUE CLA	Y & SANDSTO	NE STREAKS	
	SAND & CLAY STREAKS							
	COARSE & MED. SAND SANDY CLAY							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .03.18-2009 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. KWW430. This Water Well Record was completed of (mo/day/yeary 03-18-09)								
under the business name ofHoward Drilling Box 806 Beaver Ok 73932 by (signature)								
(white, blue, pink) to Kansas De	epartment of Health	and Environment, Bureau	of Water, Geo	ology Section	on, 1000 SW Jac	ckson St. Suite 420,	Topeka, Kansas 66612-1367.	
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								