


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NW 1/4 Section Number 6 Township Number T 28 S Range Number R 35 EW
 County: Grant

Distance and direction from nearest town or city street address of well if located within city? Sublette: North on Hwy 83 to Hwy 160 W on 160 18 mi, 6Mi N & E into or Hickok: 2 mi E, 6 mi N, E into (approx directions)

2 WATER WELL OWNER: SW Windmill John Weibel
 RR#, St. Address, Box # : P.O. Box 909 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Meade, Ks. 67864 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL 440 ft. ELEVATION: ft.
 Depth(s) Groundwater Encountered 1 300 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 300 ft. below land surface measured on mo/day/yr 9-15-04
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 3.80 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 24 in., weight 3.604 lbs./ft. Wall thickness or gauge No. SDR 21.316
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 380 ft. to 440 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 240 ft. to 440 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug
 Grout Intervals: From 1 ft. to 25 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Surface	302	427	Sand and gravel
1	92	Sandy clay and clay	427	432	Sandy clay
92	114	Sand and gravel	432	440	Clay "tan"
114	143	Sandy clay and clay			
143	174	Sand and gravel			
174	182	Clay			
182	193	Sand			
193	197	Clay			
197	221	Sand			
221	238	Clay			
238	245	Sand			
245	260	Clay			
260	286	Hard Sand and clay streaks			
286	302	Clay			

RECEIVED
 SEP 30 2004
 BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-15-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No KWWCL-430 This Water Well Record was completed on (mo/day/yr) 9-15-04 under the business name of Howard Drilling Co Box 806 Beaver Ok 73932 by (signature) *Phil Howard*