USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

		П	
ш_			
T	R	EW	sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health (Water Well Contractors) Forbes-Bldg. 740 Topeka, Kansas 66620

1 Location of well:	County Grant	Township name Fraction NE ¹ 4, NE ¹ 4, NE ¹ 4		Section number			Town number	Range number R36W	
	ion from nearest town or cit st & 2 3/4 Mi Il location if in city:	N. of Hickol	3 Owne	of well:	J	ohnny oute	/ Boylan		
Locate with "X" in section below: N Sketch map:					u	1ysses, Kansas 67880 4 Well depth: 450 ft. Date of completion Well diameter 26 in.			
* NE ¹ / ₄	3 3	est side	· ν _		5				
Hickok • 2 mi. East						7 Casing: Material Stee Height: above below Threaded Welded Surface 12 in. Djam. Weight 34.5 lbs./ft			
2	•	e and color of material		From	То	in. to ft. depth			
Surface 8	Brown Clay			0	15	Ma	nufacturer <u>John</u> e Galvanized (
Brown Cla	•			15	30	Slot/games 100×100 Length 100 ft. Set between 275 ft. and 315 ft. 375 \$ 435			
Sand				30	75	Fittings: * See remarks Gravel pack X Yes No Size range of material 4 down			
Brown Clay				75	90	9 Static water level: 257_ft. below land surface Date 3—8—76			
_Snad				90	165	10 Pur	nping level below land sur 20 ft. after <u>2</u> hrs	faces: - . pumping 800 g.p.m.	
Brown Cla	ay			165	195	ft. after hrs. pumping g.p.m. Estimated maximum yield 1200 g.p.m.			
Blue Cla	у			195	235	_	ter sample submitted: Yes 🔀 No Dat		
Coarse S	and			235	315	_	ll head completion: Pitless adapter	12 in. Inches above grade	
Brown Cl.	•				360		Il grouted? X Yes Neat cement X Bentoni	No ite	
Blue Cla					375	<u> </u>	oth: From _O ft. to		
Coarse R					442 450		Direction Direction Output Direction Output Direction Direction Direction Direction		
	Blwe Clay				480		nufacturer's name <u>GC</u>	Not installed	
						Mo Lei		HP _200Volts ft. capacit 200 g.m.p.	
							Submersible	X Turbine	
	 	e a second sheet if needed					Certrifugal	☐ Reciprocating ☐ Other	
Drilling Sub-contracted to: Minter-Wilson Drilling Co. License #208 Topography: Garden City, Kansas 67846 HIII * Lakewood - Perf Slot - 125 X 66 Slope Set between 315' & 375', 435' & 450' Upland						Thi rep K Bus Ad	ter well contractor's certical swell was drilled under more is true to the best of management of the services and the services and the services are services	y jurisdiction and this by knowledge and belief. Co., Inc. 263 License No. 11 ysses, Kn. 6788	
Valley							Authorized repres		