USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

		ıı	
\Box			
т	D	E\A/	sec 1/4 1/4 1/4 No.
		LYY	SEC 1/4 1/4 1/4 1NO.

Kansas State Dept. Of Health (Water Well Contractors) Forbes-Bldg. 740 Topeka, Kansas 66620

ſ		County	Township name	Fraction	-	Section number			Town number	Range number		
	1 Location of well:	Grant	Sherman	SE SE	NW	31			28 S	36 W		
	Distance and directi	Distance and direction from nearest town or city: 1 mile east ½ north ^{3 Owner of w}								tee for Kansas		
	Street address of well located fir Hickok, Ks. Address: Ch								tian Home, Inc.			
l	Locate with "X" in section below: N I I I I I I I I I I I I I I I I I I						sses,	Kansas 67880 4 Well depth: 482 ft. Date of completion 28/				
								Well diameter <u>27</u> in.				
								5 Cable tool X Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary				
	W								6 Use: Domestic Public supply Industry Itrigation Air conditioning Commercial Test well			
l	2	Typ	e and color of material			From	То		in. toft. depth			
ŀ	Type and color of material							8 Sc M	reen: anufacturer <u>Lakewo</u>	od		
-	Surfac	е				0	2	Ту	Type <u>stee1</u> Dia. <u>16''</u>			
۱	Sandy clay						45	SI Se	ot/gauze <u>3/16</u> L t From 214 ff. and	428		
	Modium	to coarse sa	nd and gravel			45	58	Fit Gr	Fittings: 1/4 to 5/8 Gravel packed Yes No Size range of material			
		clay w/sand s					127	9 Sto				
·	-					107	160					
	Brown	gummy clay				127	160	10 Pu 310	10 Pumping level below land surfaces: 10 ft. after 12.7 hrs. pumping 1300 g			
214-	Rlue a	nd brown gumm	y clay			160-	262	l _	ft. after hrs.	pumping g.p.m.		
	Embedded sand & clay					262	294	-	ater sample submitted:	g.p.m.		
		-				204	700	—	Yes No Date			
		to coarse sa		1		<u>294</u>		1 —	12 Well head completion: Pitless adapter Inches above grade			
	Medium	to coarse sa	ind w/small cl	ay break	cers	322	388	13 W	ell grouted? X Yes	□N₀		
							400	L ₂	Neat cement Bentoni	te [] [2] ft.		
							417	$\overline{}$		southwest hou		
428	Place & hours shale w/womy fine cond					417 [°]	469	ft W	Direction ell disinfected upon comple	trion? Yes No		
1-8	Blue & brown shale w/very fine sand Blue & brown shale and sandrock loose							15 Pu	_	Not installed		
						469	483	Manufacturer's name HP _				
	Blue 8	f brown shale	tight			-		4	Length of drop pipe ft. capacity			
								∸ ا	/pe:] Submersible [Turbine		
		fuse	e a second sheet if needed	1]] Jet] Certrifugal [Reciprocating Other		
	(use a second sneet it naeded) 16 Remarks: elevation							17 W	ater well contractor's certif	-		
Wheat field								1	is well was drilled under m port is true to the best of m	· ·		
	Topography: HiII Slope							1	ouck Bros Dr			
								Bu	siness name ddress Bay 487, 7	a License No.		
	Upland				_				gned Market Be Authorized represe	ald Date 3/28/1		
	☐ Valley							1	Authorized represe	ALL COLOR		