


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 20 Township Number T 28 S Range Number R 36 EW
 County: Grant

Distance and direction from nearest town or city street address of well if located within city? From Jct. of Hwy. 160 and 25 in Ulysses. 1 North on Hwy 25, 4 East on blacktop and Northeast into on East side of house

2 WATER WELL OWNER: Bernie Lafever
 RR#, St. Address, Box # : 4042 E. Rd. 11
 City, State, ZIP Code : Ulysses, Ks. 67880
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 380 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 240 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 240 ft. below land surface measured on mo/day/yr 3-30-05
 Pump test data: Well water was 300 ft. after hours pumping 35 gpm
 Est. Yield 35 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded
 Blank casing diameter 5 in. to 360 Dia in. to ft. Dia in. to ft.
 Casing height above land surface 24 in., weight 3.904 lbs./ft. Wall thickness or gauge No SDR 21.316
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Guazed wrapped 7 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 360 ft. to 380 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 180 ft. to 380 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole plug
 Grout Intervals: From 1 ft. to 25 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Surface			
1	8	Sandy clay			
8	78	Sandy clay and clay			
78	97	Clay			
97	119	Sandy clay			
119	152	Clay			
152	163	Clay and sandy clay			
163	290	Clay			
290	319	Sandy clay			
319	332	Clay			
332	364	Sandy clay and sand streaks			
364	380	Sand and sandy clay streaks			
380	400	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-30-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. KWWCL-430. This Water Well Record was completed on (mo/day/yr) 3-30-05 under the business name of Howard Drilling Co Box 806 Beaver, Ok. 73932 by (signature) *[Signature]*