

USE TYPEWRITER OR BALL POINT PEN—PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

Kansas Department of Health and Environment—Division of Environment (Water well Contractors)  
Topeka, Kansas 66620

<b>1. Location of well:</b>	County <b>Grant</b>	Fraction <b>SE SE SE</b> 1/4 1/4 1/4	Section number <b>17</b>	Township number <b>28</b> T S R	Range number <b>37</b> E W
<b>2. Distance and direction from nearest town or city:</b>	<b>from the four way stop at Ulysses 1n-1w-1n-1/2w</b>		<b>3. Owner of well: Bill Rogers</b>		
Street address of well location if in city:		R.R. or street: <b>Box 492</b>			
		City, state, zip code: <b>Ulysses, Ks. 67880</b>			
<b>4. Locate with "X" in section below:</b>		<b>Sketch map:</b>			
<b>5. Type and color of material</b>		From		To	
<b>Surface</b>		0		2=	
<b>Sandy clay</b>		2		48	
<b>Fine to coarse sand w/clay breakers</b>		48		70	
<b>Brown sandy clay w/very fine sand strips</b>		70		128	
<b>Brown &amp; gray clay, emb edded sand strips</b>		128		234	
<b>Fine to coarse emb edded sand and gravel, brown clay &amp; lime shells</b>		234		257	
<b>Brown sandy clay, very fine sand w/lime shells</b>		257		374	
<b>Fine to coarse sand (tight)w/loose strips some clay breakers</b>		374		391	
<b>Tight sand, strips of brown brown clay &amp; sand rock</b>		391		400	
(Use a second sheet if needed)					
<b>18. Elevation:</b>		<b>19. Remarks:</b>		<b>20. Water well contractor's certification:</b>	
Topography: Hill <input checked="" type="checkbox"/> Slope Upland Valley				This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <b>Houck Bros. Drlg. Co. 164</b> Business name <b>487, Ulysses, Ks.</b> License No. Address <b>Box</b> Signed <b>M. Beard</b> Date <b>5/20/78</b> Authorized representative	

**6. Bore hole dia** 9 1/4 in. **Completion date** \_\_\_\_\_  
**Well depth** 400 ft. **5/2/78**

**7. Cable tool**  Rotary  Driven  Dug  
 Hollow rod  Jetted  Bored  Reverse rotary

**8. Use:**  Domestic  Public supply  Industry  
 Irrigation  Air conditioning  Stock  
 Lawn  Oil field water  Other

**9. Casing: Material** styrene **Height:** (Above or below) 18 in.  
glued and rivet  
Threaded  Welded  Surface   
RMP  PVC  Weight \_\_\_\_\_ lbs./ft.  
Dia. 5 in. to 370 ft. depth Wall Thickness: inches or  
Dia. \_\_\_\_\_ in. to \_\_\_\_\_ ft. depth gage No. 320

**10. Screen: Manufacturer's name** \_\_\_\_\_  
**Sunflower**  
Type Styrene Dia. 5"  
Slot/gauze 1/16" Length 30  
Set between 370 ft. and 400 ft.  
1 ft. and 1/4 ft.  
Gravel pack?  Size range of material \_\_\_\_\_

**11. Static water level:** 243 ft. below land surface Date 5/20/78

**12. Pumping level below land surfaces:**  
253 ft. after 10 hrs. pumping 18 g.p.m.  
\_\_\_\_\_ ft. after \_\_\_\_\_ hrs. pumping \_\_\_\_\_ g.p.m.  
Estimated maximum yield 30 g.p.m.

**13. Water sample submitted:** \_\_\_\_\_ mo./day/yr.  
Yes  No  Date \_\_\_\_\_

**14. Well head completion:**  
 Pitless adapter 20 inches above grade

**15. Well grouted?**   
With:  Neat cement  Bentonite  Concrete  
Depth: From 0 ft. to 10 ft.

**16. Nearest source of possible contamination:**  
ft. \_\_\_\_\_ Direction \_\_\_\_\_ Type field  
Well disinfected upon completion?  Yes  No

**17. Pump:**  Not installed  
Manufacturer's name \_\_\_\_\_  
Model number \_\_\_\_\_ HP \_\_\_\_\_ Volts \_\_\_\_\_  
Length of drop pipe \_\_\_\_\_ ft. capacity \_\_\_\_\_ g.p.m.  
Type:  
 Submersible  Turbine  
 Jet  Reciprocating  
 Centrifugal  Other

28 37 W 17 SE SE SE SE  
1/4 1/4 1/4 1/4