Distance and direction from neare APPROX. 3.0 MILES NORTH AND 7.0 N	MILES WEST								
WATER WELL OWNER: COCKRE RR#, St. Address, Box # : 201 WE City, State, ZIP code : JOHNS	EST LOGAN ON, KS	67855-			Agricult ion Numbe			ater Resou	rces
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			TED WELL 273 vater Encounter	ELEVA red 1	TION: . 245 f	0 t. 2.	0 ft	. 3.	0
	1 1	'S STATIC WATE Pump tes	ER LEVEL 245 stdata: Well w						
		mated Yield	0 gpm: Weil	water was	0 ft.	after	0 hours	pumping	0
W	1 1			in. to	0 ft., a	nd	in. to	0 ft.	
		. WATER WAS: 02	2 IRRIGATION						1
SW SE		a chemical/bac	cteriological	sample subm	itted to	departmen	nt? No ;		
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MA SCREEN OR PERFORATION OPENINGS A	EEL in. to 2: -36 in., TERIAL: 01	STEEL (NOWN 0 ft. to	JOINTS: WELDE in. to 0 lbs/ft.	bmitted D	Dia cness or g	in. to auge No.	Water wel	l disinfec	ted?
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MA SCREEN OR PERFORATION OPENINGS A	Was - EEL in. to 2 - 36 in., TERIAL: 01	CASING 273 ft., Dia weight STEEL KNOWN Oft. to Oft. to Oft. to	JOINTS: WELDE in. to 0 lbs/ft.	bmitted Oft., Wall thich oft. oft. oft.	Dia (ness or g	in. to auge No.	Water wel		ted?
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface Type of Screen or Perforation ma Screen or Perforation openings a Screen Perforated Intervals: Gravel Pack Intervals: Grout material 02 cement grou Grout intervals: From 3 ft.	EEL in. to 2 -36 in., TERIAL: 01 From From From	CASING PT3 ft., Dia Weight STEEL CHOWN Oft. to Oft. to Oft. to Oft. to Oft. to	JOINTS: WELDE in. to 0 lbs/ft. 0 ft., Fro 0 ft., Fro 0 ft., Fro	bmitted Oft., Wall thich oft. oft. oft.	Dia (ness or g	in. to auge No.	Oft.		
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface Type of Screen or Perforation ma Screen or Perforation openings a Screen Perforated Intervals: Gravel Pack Intervals: Grout material 02 cement grou Scrout intervals: From 3 ft.	EEL in. to 2 -36 in., TERIAL: 01 From From From	CASING TOTAL CASIN	JOINTS: WELDE in. to 0 lbs/ft. 0 ft., Fro 0 ft., Fro 0 ft., Fro	bmitted Oft., Wall thick Oft. Oft. Oft. Oft.	Dia cness or g	in. to auge No. Ift. Ift. Ift. Ift.	O ft. Helper well	ow many fee	
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface Type Of Screen or Perforation ma Screen or Perforation openings a Screen Perforated Intervals: Gravel Pack Intervals: Grout Material 02 Cement Grou Scrout Intervals: From 3 ft. What is the nearest source of po Direction from well?	EEL in. to 2 -36 in., ITERIAL: 01 From From From From From Sto 6 in.,	CASING TOTAL CASIN	JOINTS: WELDER in. to 0 lbs/ft. 0 ft., Fro	bmitted Oft., Wall thick oft. oft. ft. ft. FROM: 3: 6;	Dia (ness or g	in. to auge No. Ift. Ift. Ift. COPSOIL CENENT GR	O ft. Oft. HOPLUGGING	ow many fee	
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MA SCREEN OR PERFORATION OPENINGS A SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 02 CEMENT GROUG Grout intervals: From 3 ft. What is the nearest source of po Direction from well?	EEL in. to 2 -36 in., ITERIAL: 01 From From From From From Sto 6 in.,	CASING TOTAL CASIN	JOINTS: WELDER in. to 0 lbs/ft. 0 ft., Fro	bmitted Oft., Wall thick oft. oft. ft. ft. FROM: 3: 6;	Dia (ness or g	in. to auge No. Ift. Ift. Ift. COPSOIL CENENT GR	O ft. Oft. HOPLUGGING	ow many fee	
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MA SCREEN OR PERFORATION OPENINGS A SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 02 CEMENT GROUGerout intervals: From 3 ft. What is the nearest source of po Direction from well?	EEL in. to 2 -36 in., ITERIAL: 01 From From From From From Sto 6 in.,	CASING TOTAL CASIN	JOINTS: WELDER in. to 0 lbs/ft. 0 ft., Fro	bmitted Oft., Wall thick oft. oft. ft. ft. FROM: 3: 6;	Dia (ness or g	in. to auge No. Ift. Ift. Ift. COPSOIL CENENT GR	O ft. Oft. HOPLUGGING	ow many fee	
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MA SCREEN OR PERFORATION OPENINGS A SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 02 CEMENT GROUGerout intervals: From 3 ft. What is the nearest source of po Direction from well?	EEL in. to 2 -36 in., ITERIAL: 01 From From From From From Sto 6 in.,	CASING TOTAL CASIN	JOINTS: WELDER in. to 0 lbs/ft. 0 ft., Fro	bmitted Oft., Wall thick oft. oft. ft. ft. FROM: 3: 6;	Dia (ness or g	in. to auge No. Ift. Ift. Ift. COPSOIL CENENT GR	O ft. Oft. HOPLUGGING	ow many fee	