WATER WELL OWNER:	DALE S	STEVENSON								
RR#, St. Address,	Box # : 1169 W	N. ROAD 8			Board o	of Agric	ulture, Di	vision of	Water Res	ources
City, State, ZIP c	ode : ULYSSE	ES, KS	57880 - 		Applica	ation Nu	mber: 6T 2	2.D1		
LOCATE WELL'S LOCA AN "X" IN SECTION			PTH OF COMPLET oth(s) Groundw				0 9 ft.	2. 0	ft. 3.	0 f
\	: : : : -: NE	1 1	'S STATIC WATE Pump tes	R LEVEL 99 tdata: W ell						
	: 14L		mated Yield	0 gpm: Wel	l water was	5 0	ft. after	0 hou	rs pumping	0 g
W	; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	-! E	Hole Diameter	•	in. to	0 ft.	, and	in. to	0 ft.	
! ;	i i i i i i i i i i i i i i i i i i i		WATER WAS: 02	IRRIGATION						į
' CM	_' CE	_ ;								
/ ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	NG USED: 01 STI ter 16 e land surface PERFORATION MA	Was If ye	0 ft., Dia weight	JOINTS: WELD	ubmitted ED O ft.,	 Dia	in. to	Water w	ell disinf	ected? Y
TYPE OF BLANK CASI Blank casing diame Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORAT	NG USED: 01 STI ter 16 e land surface PERFORATION MA ION OPENINGS A	EEL in. to -48 in., TERIAL: 01: RE: UNK	CASING Oft., Dia weight STEEL NOWN Oft. to	JOINTS: WELD in. to 0 lbs/ft.	ubmitted ED Oft., Wall thic	Dia ckness c	in, to or gauge No 0 ft.	Water w	ell disinf	ected? Y
TYPE OF BLANK CASI Blank casing diame Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORATED GRAVEL PACK	NG USED: 01 STI ter 16 e land surface PERFORATION MA ION OPENINGS A	EEL in. to -48 in., TERIAL: 01 !	CASING Oft., Dia weight STEEL NOWN Oft. to Oft. to Oft. to	JOINTS: WELD in. to 0 lbs/ft. 0 ft., Fr 0 ft., Fr	ubmitted ED Oft., Wall this on Ofform Ofform Ofform Ofform	Dia ckness c t. to t. to t. to	in, to or gauge No 0 ft.	Water w	ell disinf	ected? Y
/ ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	NG USED: 01 STI ter 16 e land surface PERFORATION MA ION OPENINGS A INTERVALS: INTERVALS: 02 CEMENT GROUFOR 3 ft. t source of po	EEL in. to -48 in., TERIAL: 01 ! RE: UNK From From From From T	CASING Oft., Dia weight STEEL NOWN Oft. to Oft. to Oft. to Oft. to	JOINTS: WELD in. to 0 lbs/ft. 0 ft., Fr 0 ft., Fr 0 ft., Fr	ubmitted ED Oft., Wall thic on Off om Off om Off	Dia ckness c t. to t. to t. to t. to	in, to or gauge No 0 ft. 0 ft. 0 ft.	Water w	ell disinf	
TYPE OF BLANK CASI Blank casing diame Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORATED GRAVEL PACK GROUT MATERIAL Grout Intervals: What is the neares	NG USED: 01 STI ter 16 e land surface PERFORATION MA ION OPENINGS A INTERVALS: INTERVALS: O2 CEMENT GROU From 3 ft.	EEL in. to -48 in., TERIAL: 01 ! RE: UNK From From From From T	CASING Oft., Dia weight STEEL NOWN Oft. to Oft. to Oft. to Oft. to Oft. to	JOINTS: WELD in. to 0 lbs/ft. 0 ft., Fr 0 ft., Fr 0 ft., Fr	ubmitted ED Oft., Wall thic on Off om Off om Off	Dia ckness of t. to t. to t. to t. to	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft.	Water w	ell disinf	feet?
TYPE OF BLANK CASI Blank casing diame Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORATE GRAVEL PACK GROUT MATERIAL Grout Intervals: What is the neares Direction from wel	NG USED: 01 STI ter 16 e land surface PERFORATION MA ION OPENINGS A INTERVALS: INTERVALS: O2 CEMENT GROU From 3 ft.	EEL in. to -48 in., TERIAL: 01: From From From From T to 13 f	CASING Oft., Dia weight STEEL NOWN Oft. to Oft. to Oft. to Oft. to Oft. to	JOINTS: WELD in. to 0 lbs/ft. 0 ft., Fr 0 ft., Fr 0 ft., Fr	ubmitted ED Oft., Wall thic om Off om Off om Of	Dia ckness c	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft.	Water w O ft O ft.	ell disinf	feet?
TYPE OF BLANK CASI Blank casing diame Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORATE GRAVEL PACK GROUT MATERIAL Grout Intervals: What is the neares Direction from wel	NG USED: 01 STI ter 16 e land surface PERFORATION MA ION OPENINGS A INTERVALS: INTERVALS: O2 CEMENT GROU From 3 ft.	EEL in. to -48 in., TERIAL: 01: From From From From T to 13 f	CASING Oft., Dia weight STEEL NOWN Oft. to Oft. to Oft. to Oft. to Oft. to	JOINTS: WELD in. to 0 lbs/ft. 0 ft., Fr 0 ft., Fr 0 ft., Fr	ubmitted ED Oft., Wall thic om Off om Off om Off om Off FROM: Off., 1	Dia ckness c	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft. CEMENT (CLAY	Water w O ft O ft.	ell disinf	feet?
TYPE OF BLANK CASI Blank casing diame Casing height abov TYPE OF SCREEN OR SCREEN OR PERFORATE GRAVEL PACK GROUT MATERIAL Grout Intervals: What is the neares Direction from wel	NG USED: 01 STI ter 16 e land surface PERFORATION MA ION OPENINGS A INTERVALS: INTERVALS: O2 CEMENT GROU From 3 ft.	EEL in. to -48 in., TERIAL: 01: From From From From T to 13 f	CASING Oft., Dia weight STEEL NOWN Oft. to Oft. to Oft. to Oft. to Oft. to	JOINTS: WELD in. to 0 lbs/ft. 0 ft., Fr 0 ft., Fr 0 ft., Fr	Ubmitted ED Oft., Wall thic Om Off Om Off Om Off Om Off Oft., FROM (0 ; 3 ; 13 ; 0 ;	Dia ckness cont. to t. to t. to t. to t. to t. to t. 10 13 13 13 10 10 10 10 10 10 10 10 10 10 10 10 10	in, to gauge No O ft. O ft. O ft. O ft. TOPSOIL CEMENT (CLAY	Water w O ft O ft.	ell disinf	feet?