

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Stanton	Fraction SE 1/4 SW 1/4 NW 1/4	Section number 21	Township number T 28 S	Range number R 39
----------------------	--------------------------	---	-----------------------------	----------------------------------	-----------------------------

2. Distance and direction from nearest town or city: from Standard Service station at Ulysses, Ks. 13 miles west-1 1/2 north	3. Owner of well: Elmer Kendrick Johnson, Ks. 67855
Street address of well location if in city:	R.R. or street:
	City, state, zip code:

4. Locate with "X" in section below: Sketch map:

N

1 Mile

NW	NE
X	SE

1 Mile

S

5. Type and color of material	From	To
Surface	0	2
Very fine sand w/clay breakers	2	18
Sandy clay w/fine sand strips	18	50
Medium to coarse sand w/clay breakers	50	82
Brown clay	82	184
Tine to medium sand w/clay breakers	184	208
Sandy clay w/very fine sand strips	208	255
Very fine to fine sand w/clay breakers	255	277
Sandy clay, lime shale & fine sand strips	277	287
Medium to coarse sand w/clay breakers	287	313
Sandy clay w-lime shale & very fine sand	313	364
Very fine to medium coarse sand w/sandy clay strip	364	377
Brown shale, lime shale, sandrock & Dakota	377	405
Brown & blue shale	405	434
Brown and blue shale w/dakota	434	467
Brown & blue shale w/Dakota	467	502
(Use a second sheet if needed)		

6. Bore hole dia. 27 in. Completion date _____
Well depth 502 ft. 2/23/77

7. Cable tool Rotary Driven Dug
 Hollow rod Jetted Bored Reverse rotary

8. Use: Domestic Public supply Industry
 Irrigation Air conditioning Stock
 Lawn Oil field water Other

9. Casing: Material steel Height: Above or below
Threaded _____ Welded Surface 12 in.
RMP _____ PVC _____ Weight 36.8 lbs./ft.
Dia. 16 in. to 235.7 ft. depth; Wall Thickness: inches or
Dia. _____ in. to _____ ft. depth; gage No. .219

10. Screen: Manufacturer's name Lakewood Pipe of Texas
Type steel Dia. 16"
Slot/gauze 3/16" Length 266.5'
Set between 235.7 ft. and 502 ft.
_____ ft. and _____ ft.
Gravel pack? Size range of material 1/4 x 5/8"

11. Static water level: _____ mo./day/yr.
161 ft. below land surface Date 2-18-77

12. Pumping level below land surfaces:
410 ft. after 35.8 hrs. pumping 860 g.p.m.
_____ ft. after _____ hrs. pumping _____ g.p.m.
Estimated maximum yield 900 g.p.m.

13. Water sample submitted: _____ mo./day/yr.
Yes No _____ Date _____

14. Well head completion:
 Pitless adapter 12 inches above grade

15. Well grouted?
With: Neat cement Bentonite Concrete
Depth: From 0 ft. to 10 ft.

16. Nearest source of possible contamination:
ft. _____ Direction _____ Type field
Well disinfected upon completion? _____ Yes No

17. Pump: Not installed
Manufacturer's name _____
Model number _____ HP _____ Volts _____
Length of drop pipe _____ ft. capacity _____ g.p.m.
Type:
 Submersible Turbine
 Jet Reciprocating
 Centrifugal Other

18. Elevation:	19. Remarks:
Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley	

20. Water well contractor's certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Houck Bros. Drlg. Co. 164
Business name License No.
Address **Box 487, Ulysses, Ks.**

Signed M. Beard Date 5/25/77
Authorized representative

T
R
E
S
E
C
1/4 1/4 1/4
 28-39-21
 SECTION 21