


1 LOCATION OF WATER WELL: Fraction SE 1/4 SW 1/4 SW 1/4 Section Number 35 Township Number T 28 S Range Number R 39 E(N)
 County: Stanton
 Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Johnson Co-op Grain
 RR#, St. Address, Box #: 304 E. Highland Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Johnson, Ks. 67855-Big Bow SB-6 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 228 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 178.7 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter in. to 228 ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded X
 Blank casing diameter in. to 196 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface in., weight 2.071 lbs./ft. Wall thickness or gauge No. 237
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 196 ft. to 228 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 176 ft. to 228 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 to 2 ft., From 2 ft. to 170 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage Removed Fuel Storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Surface	120	125	Sandy Clay w/Sand Strks.
3	6	Lt. Brn. Silty Clay	125	130	Sand w/Clay & Caliche Strks.
6	16	Med. Clay/Slightly Silty	130	162	Sandy Clay & Calich w/Some
16	31	Clay/Silty to Sandy	162	163	Sand Fine Sand Strks.
31	38	Clay w/Caliche	163	164	Caliche
38	38.5	Solid Caliche w/Dense Clay	164	180	Clay & Caliche Mix
38.5	45	Clay & Caliche	180	184	Fine Sand & Clay Strks.
45	59	Sandy Clay & Caliche Strks.	184	191	Clay & Sand Strks.
59	71	Fine Sand w/Clay Strks.	191	201	Sandy Clay
71	76	Sandy Clay w/Fine Sand Strks.	201	202	Sand
76	80	Sandy Clay & Caliche Strks.	202	207	Sticky Clay
80	101	Fine Sand & Clay Strks.	207	220	Sand & Clay Mix
101	104	Sandy Sticky Clay	220	228	Sand
104	115	Sand & Sandy Clay & CalicheSt.			
115	120	Sticky Sandy Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-17-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 3-23-94 under the business name of Woofter Pump & Well, Inc. by (signature) Jay G. Woofter