

1 LOCATION OF WATER WELL: County: Adair Fraction: SW 1/4 NW 1/4 NE 1/4 Section Number: 8 Township Number: 280 Range Number: 4 E/W: W

Distance and direction from nearest town or city street address of well if located within city? see below

2 WATER WELL OWNER: Dan Robertson

RR#, St. Address, Box #: 555 Jefferson Board of Agriculture, Division of Water Resources

City, State, ZIP Code: Cheney, W 67025 Application Number: 80

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

Diagram showing a 36-section grid with 'X' in the NE section. North arrow and 1 mile scale bar.

4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 7-1602 ft.

Depth(s) Groundwater Encountered: 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL: 19 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 20 ft. after 80 hours pumping 11 gpm

Est. Yield: 20 gpm: Well water was 80 ft. after 80 hours pumping 11 gpm

Bore Hole Diameter: 11 in. to 80 ft., and 80 in. to 80 ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Oil field water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)	9 Dewatering	12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes X No 1; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No 1

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped <u>1</u>
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <u>1</u> Threaded <u>1</u>

Blank casing diameter: 5 in. to 20 ft., Dia. 2.40 in. to 160 ft.

Casing height above land surface: 12 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 160 ft.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 20 ft. to 80 ft., From 80 ft. to 80 ft.

GRAVEL PACK INTERVALS: From 19 ft. to 80 ft., From 80 ft. to 80 ft.

6 GROUT MATERIAL: 1 Heat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 80 ft. to 19 ft., From 19 ft. to 80 ft., From 80 ft. to 80 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? North How many feet? 12

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-16-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/yr) 7-17-02 under the business name of Weninger Drilling Inc. by (signature) Dickie Gorges

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.